

---

# **tox Documentation**

*Release 2.8.2*

**holger krekel**

**Sep 10, 2017**



|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>vision: standardize testing in Python</b>                                | <b>1</b> |
| <b>2</b> | <b>What is Tox?</b>   | <b>3</b> |
| <b>3</b> | <b>Basic example</b>  | <b>5</b> |
| <b>4</b> | <b>Current features</b>   | <b>7</b> |
| 4.1      | tox installation . . . . .  | 8        |
| 4.2      | tox configuration and usage examples . . . . .                              | 8        |
| 4.3      | tox configuration specification . . . . .                                   | 23       |
| 4.4      | Other Rules and notes . . . . .   | 32       |
| 4.5      | V2: new tox multi-dimensional, platform-specific configuration . . . . .    | 32       |
| 4.6      | Issues with current tox (1.4) configuration . . . . .                       | 33       |
| 4.7      | Goals, resolving those issues . . . . .                                     | 33       |
| 4.8      | Example: Generating and selecting variants . . . . .                        | 33       |
| 4.9      | The new “platform” setting . . . . .  | 34       |
| 4.10     | Expanding the <code>envlist</code> setting . . . . .                        | 35       |
| 4.11     | Templating based on environments names . . . . .                            | 35       |
| 4.12     | Showing all expanded sections . . . . .                                     | 35       |
| 4.13     | Making sure your packages installs with <code>easy_install</code> . . . . . | 35       |
| 4.14     | Default settings related to environments names/variants . . . . .           | 35       |
| 4.15     | Use more bash-style syntax . . . . .  | 36       |
| 4.16     | Transforming the examples: <code>django-rest</code> . . . . .               | 36       |
| 4.17     | Transforming the examples: <code>django-treebeard</code> . . . . .          | 36       |
| 4.18     | support and contact channels . . . . .                                      | 37       |
| 4.19     | Changelog history . . . . .   | 37       |
| 4.20     | tox plugins . . . . .   | 50       |
| 4.21     | Writing a json result file . . . . .  | 54       |
| 4.22     | tox 0.5: a generic virtualenv and test management tool for Python . . . . . | 55       |
| 4.23     | tox 1.0: the rapid multi-python test automatizer . . . . .                  | 55       |
| 4.24     | tox 1.1: the rapid multi-python test automatizer . . . . .                  | 56       |
| 4.25     | tox 1.2: the virtualenv-based test run automatizer . . . . .                | 57       |
| 4.26     | tox 1.3: the virtualenv-based test run automatizer . . . . .                | 57       |
| 4.27     | tox 1.4: the virtualenv-based test run automatizer . . . . .                | 58       |
| 4.28     | tox 1.4.3: the Python virtualenv-based testing automatizer . . . . .        | 59       |
| 4.29     | CHANGELOG . . . . .   | 60       |
| 4.30     | tox 1.8: Generative/combinatorial environments specs . . . . .              | 60       |

|      |  |    |
|------|--|----|
| 4.31 | tox-1.9: refinements, fixes (+detox-0.9.4) | 61 |
| 4.32 | tox-2.0: plugins, platform, env isolation  | 62 |
| 4.33 | 2.4.0                                      | 64 |
| 4.34 | Less announcing, more changelogging        | 64 |

|                            |           |
|----------------------------|-----------|
| <b>Python Module Index</b> | <b>65</b> |
|----------------------------|-----------|

# CHAPTER 1

---

vision: standardize testing in Python

---

`tox` aims to automate and standardize testing in Python. It is part of a larger vision of easing the packaging, testing and release process of Python software.



## CHAPTER 2

---

### What is Tox?

---

Tox is a generic `virtualenv` management and test command line tool you can use for:

- checking your package installs correctly with different Python versions and interpreters
- running your tests in each of the environments, configuring your test tool of choice
- acting as a frontend to Continuous Integration servers, greatly reducing boilerplate and merging CI and shell-based testing.





## CHAPTER 3

---

### Basic example

---

First, install `tox` with `pip install tox`. Then put basic information about your project and the test environments you want your project to run in into a `tox.ini` file residing right next to your `setup.py` file:

```
# content of: tox.ini , put in same dir as setup.py
[tox]
envlist = py26,py27
[testenv]
deps=pytest      # install pytest in the venvs
commands=pytest # or 'nosetests' or ...
```

You can also try generating a `tox.ini` file automatically, by running `tox-quickstart` and then answering a few simple questions.

To `sdist-package`, install and test your project against Python2.6 and Python2.7, just type:

```
tox
```

and watch things happening (you must have `python2.6` and `python2.7` installed in your environment otherwise you will see errors). When you run `tox` a second time you'll note that it runs much faster because it keeps track of virtualenv details and will not recreate or re-install dependencies. You also might want to checkout [tox configuration and usage examples](#) to get some more ideas.



---

## Current features

---

- **automation of tedious Python related test activities**
- **test your Python package against many interpreter and dependency configs**
  - automatic customizable (re)creation of `virtualenv` test environments
  - installs your `setup.py` based project into each virtual environment
  - test-tool agnostic: runs `pytest`, `nose` or `unittests` in a uniform manner
- *(new in 2.0) plugin system* to modify tox execution with simple hooks.
- uses `pip` and `setuptools` by default. Support for configuring the installer command through `install_command=ARGV`.
- **cross-Python compatible**: CPython-2.6, 2.7, 3.2 and higher, Jython and pypy.
- **cross-platform**: Windows and Unix style environments
- **integrates with continuous integration servers** like `Jenkins` (formerly known as Hudson) and helps you to avoid boilerplatish and platform-specific build-step hacks.
- **full interoperability with devpi**: is integrated with and is used for testing in the `devpi` system, a versatile pypi index server and release managing tool.
- **driven by a simple ini-style config file**
- **documented** *examples* and *configuration*
- **concise reporting** about tool invocations and configuration errors
- **professionally supported**
- supports *using different / multiple PyPI index servers*

## tox installation

### Install info in a nutshell

**Pythons:** CPython 2.6-3.6, Jython-2.5.1, pypy-1.9ff

**Operating systems:** Linux, Windows, OSX, Unix

**Installer Requirements:** [setuptools](#)

**License:** MIT license

**git repository:** <https://github.com/tox-dev/tox>

### Installation with pip

Use the following command:

```
pip install tox
```

It is fine to install `tox` itself into a `virtualenv` environment.

### Install from Checkout

Consult the GitHub page to get a checkout of the git repository:

<https://github.com/tox-dev/tox>

and then install in your environment with something like:

```
python setup.py install
```

or just activate your checkout in your environment like this:

```
python setup.py develop
```

so that you can do changes and submit patches.

## tox configuration and usage examples

### Basic usage

#### a simple `tox.ini` / default environments

Put basic information about your project and the test environments you want your project to run in into a `tox.ini` file that should reside next to your `setup.py` file:

```
# content of: tox.ini , put in same dir as setup.py
[tox]
envlist = py26,py27
[testenv]
deps=pytest # or 'nose' or ...
commands=pytest # or 'nosetests' or ...
```

To sdist-package, install and test your project, you can now type at the command prompt:

```
tox
```

This will sdist-package your current project, create two `virtualenv` Environments, install the sdist-package into the environments and run the specified command in each of them. With:

```
tox -e py26
```

you can run restrict the test run to the python2.6 environment.

Available “default” test environments names are:

```
py
py2
py26
py27
py3
py33
py34
py35
py36
py37
jython
pypy
pypy3
```

The environment `py` uses the version of Python used to invoke tox.

However, you can also create your own test environment names, see some of the examples in *examples*.

### specifying a platform

New in version 2.0.

If you want to specify which platform(s) your test environment runs on you can set a platform regular expression like this:

```
platform = linux2|darwin
```

If the expression does not match against `sys.platform` the test environment will be skipped.

### whitelisting non-virtualenv commands

New in version 1.5.

Sometimes you may want to use tools not contained in your virtualenv such as `make`, `bash` or others. To avoid warnings you can use the `whitelist_externals` testenv configuration:

```
# content of tox.ini
[testenv]
whitelist_externals = make
                    /bin/bash
```

### depending on requirements.txt or defining constraints

New in version 1.6.1.

(experimental) If you have a `requirements.txt` file or a `constraints.txt` file you can add it to your `deps` variable like this:

```
deps = -rrequirements.txt
```

or

```
deps = -cconstraints.txt
```

or

```
deps = -rrequirements.txt -cconstraints.txt
```

All installation commands are executed using `{toxindir}` (the directory where `tox.ini` resides) as the current working directory. Therefore, the underlying `pip` installation will assume `requirements.txt` or `constraints.txt` to exist at `{toxindir}/requirements.txt` or `{toxindir}/constraints.txt`.

This is actually a side effect that all elements of the dependency list is directly passed to `pip`.

For more details on `requirements.txt` files or `constraints.txt` files please see:

- [https://pip.pypa.io/en/stable/user\\_guide/#requirements-files](https://pip.pypa.io/en/stable/user_guide/#requirements-files)
- [https://pip.pypa.io/en/stable/user\\_guide/#constraints-files](https://pip.pypa.io/en/stable/user_guide/#constraints-files)

### using a different default PyPI url

New in version 0.9.

To install dependencies and packages from a different default PyPI server you can type interactively:

```
tox -i http://pypi.my-alternative-index.org
```

This causes `tox` to install dependencies and the `sdist` install step to use the specified url as the index server.

You can cause the same effect by this `tox.ini` content:

```
[tox]
indexserver =
    default = http://pypi.my-alternative-index.org
```

### installing dependencies from multiple PyPI servers

New in version 0.9.

You can instrument `tox` to install dependencies from different PyPI servers, example:

```
[tox]
indexserver =
    DEV = http://mypypiserver.org

[testenv]
deps =
```

```
docutils          # comes from standard PyPI
:DEV:mypackage    # will be installed from custom "DEV" pypi url
```

This configuration will install `docutils` from the default Python PYPI server and will install the `mypackage` from our DEV indexserver, and the respective `http://mypypiserver.org` url. You can override config file settings from the command line like this:

```
tox -i DEV=http://pypi.python.org/simple # changes :DEV: package URLs
tox -i http://pypi.python.org/simple     # changes default
```

## further customizing installation

New in version 1.6.

By default tox uses `pip` to install packages, both the package-under-test and any dependencies you specify in `tox.ini`. You can fully customize tox's install-command through the testenv-specific `install_command=ARGV` setting. For instance, to use pip's `--find-links` and `--no-index` options to specify an alternative source for your dependencies:

```
[testenv]
install_command = pip install --pre --find-links http://packages.example.com --no-
↳index {opts} {packages}
```

## forcing re-creation of virtual environments

New in version 0.9.

To force tox to recreate a (particular) virtual environment:

```
tox --recreate -e py27
```

would trigger a complete reinstallation of the existing `py27` environment (or create it afresh if it doesn't exist).

## passing down environment variables

New in version 2.0.

By default tox will only pass the `PATH` environment variable (and on windows `SYSTEMROOT` and `PATHEXT`) from the tox invocation to the test environments. If you want to pass down additional environment variables you can use the `passenv` option:

```
[testenv]
passenv = LANG
```

When your test commands execute they will execute with the same `LANG` setting as the one with which tox was invoked.

## setting environment variables

New in version 1.0.

If you need to set an environment variable like `PYTHONPATH` you can use the `setenv` directive:

```
[testenv]
setenv =
    PYTHONPATH = {toxindir}/subdir
```

When your test commands execute they will execute with a `PYTHONPATH` setting that will lead Python to also import from the `subdir` below the directory where your `tox.ini` file resides.

### special handling of PYTHONHASHSEED

New in version 1.6.2.

By default, Tox sets `PYTHONHASHSEED` for test commands to a random integer generated when `tox` is invoked. This mimics Python’s hash randomization enabled by default starting in [Python 3.3](#). To aid in reproducing test failures, Tox displays the value of `PYTHONHASHSEED` in the test output.

You can tell Tox to use an explicit hash seed value via the `--hashseed` command-line option to `tox`. You can also override the hash seed value per test environment in `tox.ini` as follows:

```
[testenv]
setenv =
    PYTHONHASHSEED = 100
```

If you wish to disable this feature, you can pass the command line option `--hashseed=noset` when `tox` is invoked. You can also disable it from the `tox.ini` by setting `PYTHONHASHSEED = 0` as described above.

### Integration with “setup.py test” command

**Warning:** Integrating `tox` with `setup.py test` is as of October 2016 discouraged as it breaks packaging/testing approaches as used by downstream distributions which expect `setup.py test` to run tests with the invocation interpreter rather than setting up many virtualenvs and installing packages. If you need to define `setup.py test` you can better see about integrating your eventual test runner with it, here is an [example of setup.py test integration with pytest](#). As the python eco-system rather moves away from using `setup.py` as a tool entry point it’s maybe best to not go for any `setup.py test` integration.

### Ignoring a command exit code

In some cases, you may want to ignore a command exit code. For example:

```
[testenv:py27]
commands = coverage erase
            {envbindir}/python setup.py develop
            coverage run -p setup.py test
            coverage combine
            - coverage html
            {envbindir}/flake8 loads
```

By using the `-` prefix, similar to a make recipe line, you can ignore the exit code for that command.

### Compressing dependency matrix

If you have a large matrix of dependencies, python versions and/or environments you can use *Generative envlist* and *conditional settings* to express that in a concise form:



```
[tox]
envlist = py{26,27,33}-django{15,16}-{sqlite,mysql}

[testenv]
deps =
    django15: Django>=1.5,<1.6
    django16: Django>=1.6,<1.7
    py33-mysql: PyMySQL      ; use if both py33 and mysql are in an env name
    py26,py27: urllib3      ; use if any of py26 or py27 are in an env name
    py{26,27}-sqlite: mock  ; mocking sqlite in python 2.x
```

### Prevent symbolic links in virtualenv

By default virtualenv will use symlinks to point to the system's python files, modules, etc. If you want the files to be copied instead, possibly because your filesystem is not capable of handling symbolic links, you can instruct virtualenv to use the “`--always-copy`” argument meant exactly for that purpose, by setting the `alwayscopy` directive in your environment:

```
[testenv]
alwayscopy = True
```

## pytest and tox

It is easy to integrate `pytest` runs with tox. If you encounter issues, please check if they are *listed as a known issue* and/or use the *support channels*.

### Basic example

Assuming the following layout:

```
tox.ini      # see below for content
setup.py     # a classic distutils/setuptools setup.py file
```

and the following `tox.ini` content:

```
[tox]
envlist = py26,py31

[testenv]
deps=pytest      # PYPI package providing pytest
commands=
    pytest \
        {posargs} # substitute with tox' positional arguments
```

you can now invoke `tox` in the directory where your `tox.ini` resides. `tox` will sdist-package your project, create two virtualenv environments with the `python2.6` and `python3.1` interpreters, respectively, and will then run the specified test command in each of them.

### Extended example: change dir before test and use per-virtualenv tempdir

Assuming the following layout:

```
tox.ini      # see below for content
setup.py    # a classic distutils/setuptools setup.py file
tests       # the directory containing tests
```

and the following `tox.ini` content:

```
[tox]
envlist = py26,py31
[testenv]
changedir=tests
deps=pytest
commands=
  pytest \
    --basetemp={envtmpdir} \ # pytest tmpdir setting
    {posargs} # substitute with tox' positional arguments
```

you can invoke `tox` in the directory where your `tox.ini` resides. Differently than in the previous example the `pytest` command will be executed with a current working directory set to `tests` and the test run will use the `per-virtualenv` temporary directory.

### Using multiple CPUs for test runs

`pytest` supports distributing tests to multiple processes and hosts through the `pytest-xdist` plugin. Here is an example configuration to make `tox` use this feature:

```
[testenv]
deps=pytest-xdist
changedir=tests
commands=
  pytest \
    --basetemp={envtmpdir} \
    --confcutdir=.. \
    -n 3 \ # use three sub processes
    {posargs}
```

### Known Issues and limitations

**Too long filenames.** you may encounter “too long filenames” for temporarily created files in your `pytest` run. Try to not use the “`--basetemp`” parameter.

**installed-versus-checkout version.** `pytest` collects test modules on the filesystem and then tries to import them under their [fully qualified name](#). This means that if your test files are importable from somewhere then your `pytest` invocation may end up importing the package from the checkout directory rather than the installed package.

There are a few ways to prevent this.

With installed tests (the tests packages are known to `setup.py`), a safe and explicit option is to give the explicit path `{envsitepackagesdir}/mypkg` to `pytest`. Alternatively, it is possible to use `changedir` so that checked-out files are outside the import path, then pass `--pyargs mypkg` to `pytest`.

With tests that won't be installed, the simplest way to run them against your installed package is to avoid `__init__.py` files in test directories; `pytest` will still find and import them by adding their parent directory to `sys.path` but they won't be copied to other places or be found by Python's import system outside of `pytest`.

## unittest2, discover and tox

### Running unittests with 'discover'

The `discover` project allows to discover and run unittests and we can easily integrate it in a `tox` run. As an example, perform a checkout of `Pygments`:

```
hg clone https://bitbucket.org/birkenfeld/pygments-main
```

and add the following `tox.ini` to it:

```
[tox]
envlist = py25,py26,py27

[testenv]
changedir=tests
commands=discover
deps=discover
```

If you now invoke `tox` you will see the creation of three virtual environments and a `unittest-run` performed in each of them.

### Running unittest2 and sphinx tests in one go

`Michael Foord` has contributed a `tox.ini` file that allows you to run all tests for his `mock` project, including some sphinx-based doctests. If you checkout its repository with:

```
hg clone https://code.google.com/p/mock/
```

the checkout has a `tox.ini` that looks like this:

```
[tox]
envlist = py24,py25,py26,py27

[testenv]
deps=unittest2
commands=unit2 discover []

[testenv:py26]
commands=
    unit2 discover []
    sphinx-build -b doctest docs html
    sphinx-build docs html
deps =
    unittest2
    sphinx

[testenv:py27]
commands=
    unit2 discover []
    sphinx-build -b doctest docs html
    sphinx-build docs html
deps =
    unittest2
    sphinx
```

mock uses `unittest2` to run the tests. Invoking `tox` starts test discovery by executing the `unit2 discover` commands on Python 2.4, 2.5, 2.6 and 2.7 respectively. Against Python2.6 and Python2.7 it will additionally run sphinx-mediated doctests. If building the docs fails, due to a reST error, or any of the doctests fails, it will be reported by the `tox` run.

The `[]` parentheses in the commands provide *substitutions for positional arguments in commands* which means you can e.g. type:

```
tox -- -f -s SOMEPATH
```

which will ultimately invoke:

```
unit2 discover -f -s SOMEPATH
```

in each of the environments. This allows you to customize test discovery in your `tox` runs.

## nose and tox

It is easy to integrate `nose` tests runs with `tox`. For starters here is a simple `tox.ini` config to configure your project for running with `nose`:

### Basic nose tests example

Assuming the following layout:

```
tox.ini      # see below for content
setup.py    # a classic distutils/setuptools setup.py file
```

and the following `tox.ini` content:

```
[testenv]
deps=nose
commands=
    nosetests \
        [] # substitute with tox' positional arguments
```

you can invoke `tox` in the directory where your `tox.ini` resides. `tox` will `sdist`-package your project create two `virtualenv` environments with the `python2.6` and `python2.5` interpreters, respectively, and will then run the specified test command.

### More examples?

You can use and combine other features of `tox` with your `tox` runs, e.g. *Integrating “sphinx” documentation checks*. If you figure out some particular configurations for `nose/tox` interactions please submit them.

Also you might want to checkout *General tips and tricks*.

## General tips and tricks

### Interactively passing positional arguments

If you invoke `tox` like this:

```
tox -- -x tests/test_something.py
```

the arguments after the `--` will be substituted everywhere where you specify `{posargs}` in your test commands, for example using `pytest`:

```
# in the testenv or testenv:NAME section of your tox.ini
commands =
    pytest {posargs}
```

or using `nosetests`:

```
commands =
    nosetests {posargs}
```

the above `tox` invocation will trigger the test runners to stop after the first failure and to only run a particular test file. You can specify defaults for the positional arguments using this syntax:

```
commands =
    nosetests {posargs:--with-coverage}
```

## Integrating “sphinx” documentation checks

In a `testenv` environment you can specify any command and thus you can easily integrate `sphinx` documentation integrity during a `tox` test run. Here is an example `tox.ini` configuration:

```
[testenv:docs]
basepython=python
changedir=doc
deps=sphinx
commands=
    sphinx-build -W -b html -d {envtmpdir}/doctrees . {envtmpdir}/html
```

This will create a dedicated `docs` virtual environment and install the `sphinx` dependency which itself will install the `sphinx-build` tool which you can then use as a test command. Note that `sphinx` output is redirected to the `virtualenv` environment temporary directory to prevent `sphinx` from caching results between runs.

You can now call:

```
tox
```

which will make the `sphinx` tests part of your test run.

## Selecting one or more environments to run tests against

Using the `-e ENV[, ENV2, ...]` option you explicitly list the environments where you want to run tests against. For example, given the previous `sphinx` example you may call:

```
tox -e docs
```

which will make `tox` only manage the `docs` environment and call its test commands. You may specify more than one environment like this:

```
tox -e py25,py26
```

which would run the commands of the `py25` and `py26` testenvironments respectively. The special value `ALL` selects all environments.

You can also specify an environment list in your `tox.ini`:

```
[tox]
envlist = py25,py26
```

or override it from the command line or from the environment variable `TOXENV`:

```
export TOXENV=py25,py26 # in bash style shells
```

### Access package artifacts between multiple tox-runs

If you have multiple projects using tox you can make use of a `distshare` directory where `tox` will copy in `sdist`-packages so that another tox run can find the “latest” dependency. This feature allows to test a package against an unreleased development version or even an uncommitted version on your own machine.

By default, `{homedir}/.tox/distshare` will be used for copying in and copying out artifacts (i.e. Python packages).

For project `two` to depend on the `one` package you use the following entry:

```
# example two/tox.ini
[testenv]
deps=
    {distshare}/one-*.zip # install latest package from "one" project
```

That’s all. Tox running on project `one` will copy the `sdist`-package into the `distshare` directory after which a `tox` run on project `two` will grab it because `deps` contain an entry with the `one-*.zip` pattern. If there is more than one matching package the highest version will be taken. `tox` uses `verlib` to compare version strings which must be compliant with [PEP 386](#).

If you want to use this with [Jenkins](#), also checkout the [Access package artifacts between Jenkins jobs](#).

### basepython defaults, overriding

By default, for any `pyXY` test environment name the underlying “pythonX.Y” executable will be searched in your system `PATH`. It must exist in order to successfully create `virtualenv` environments. On Windows a `pythonX.Y` named executable will be searched in typical default locations using the `C:\PythonX.Y\python.exe` pattern.

For `jython` and `pypy` the respective `jython` and `pypy-c` names will be looked for.

You can override any of the default settings by defining the `basepython` variable in a specific test environment section, for example:

```
[testenv:py27]
basepython=/my/path/to/python2.7
```

### Avoiding expensive sdist

Some projects are large enough that running an `sdist`, followed by an `install` every time can be prohibitively costly. To solve this, there are two different options you can add to the `tox` section. First, you can simply ask `tox` to please not make an `sdist`:

```
[tox]
skipsdist=True
```

If you do this, your local software package will not be installed into the virtualenv. You should probably be okay with that, or take steps to deal with it in your commands section:

```
[testenv]
commands =
    python setup.py develop
    pytest
```

Running `setup.py develop` is a common enough model that it has its own option:

```
[testenv]
usedevelop=True
```

And a corresponding command line option `--develop`, which will set `skipsdist` to `True` and then perform the `setup.py develop` step at the place where `tox` normally performs the installation of the `sdist`. Specifically, it actually runs `pip install -e .` behind the scenes, which itself calls `setup.py develop`.

There is an optimization coded in to not bother re-running the command if `$projectname.egg-info` is newer than `setup.py` or `setup.cfg`.

## Using Tox with the Jenkins Integration Server

### Using Jenkins multi-configuration jobs

The [Jenkins](#) continuous integration server allows to define “jobs” with “build steps” which can be test invocations. If you *install* `tox` on your default Python installation on each Jenkins slave, you can easily create a Jenkins multi-configuration job that will drive your `tox` runs from the CI-server side, using these steps:

- install the Python plugin for Jenkins under “manage jenkins”
- create a “multi-configuration” job, give it a name of your choice
- configure your repository so that Jenkins can pull it
- (optional) configure multiple nodes so that `tox`-runs are performed on multiple hosts
- configure axes by using `TOXENV` as an axis name and as values provide space-separated test environment names you want Jenkins/tox to execute.
- add a **Python-build step** with this content (see also next example):

```
import tox

os.chdir(os.getenv('WORKSPACE'))
tox.cmdline() # environment is selected by ``TOXENV`` env variable
```

- check Publish JUnit test result report and enter `**/junit-*.xml` as the pattern so that Jenkins collects test results in the JUnit XML format.

The last point requires that your test command creates JunitXML files, for example with `pytest` it is done like this:

```
commands = pytest --junitxml=junit-{envname}.xml
```

## zero-installation for slaves

**Note:** This feature is broken currently because “toxbootstrap.py” has been removed. Please file an issue if you’d like to see it back.

---

If you manage many Jenkins slaves and want to use the latest officially released tox (or latest development version) and want to skip manually installing tox then substitute the above **Python build step** code with this:

```
import urllib, os
url = "https://bitbucket.org/hpk42/tox/raw/default/toxbootstrap.py"
#os.environ['USETOXDEV']="1" # use tox dev version
d = dict(__file__='toxbootstrap.py')
exec urllib.urlopen(url).read() in d
d['cmdline'](['--recreate'])
```

The downloaded *toxbootstrap.py* file downloads all necessary files to install tox in a virtual sub environment. Notes:

- uncomment the line containing USETOXDEV to use the latest development-release version of tox instead of the latest released version.
- adapt the options in the last line as needed (the example code will cause tox to reinstall all virtual environments all the time which is often what one wants in CI server contexts)

## Integrating “sphinx” documentation checks in a Jenkins job

If you are using a multi-configuration Jenkins job which collects JUnit Test results you will run into problems using the previous method of running the sphinx-build command because it will not generate JUnit results. To accomodate this issue one solution is to have pytest wrap the sphinx-checks and create a JUnit result file which wraps the result of calling sphinx-build. Here is an example:

1. create a docs environment in your tox.ini file like this:

```
[testenv:docs]
basepython=python
changedir=doc # or wherever you keep your sphinx-docs
deps=sphinx
    py
commands=
    pytest --tb=line -v --junitxml=junit-{envname}.xml check_sphinx.py
```

2. create a doc/check\_sphinx.py file like this:

```
import py
import subprocess
def test_linkcheck(tmpdir):
    doctrees = tmpdir.join("doctrees")
    htmldir = tmpdir.join("html")
    subprocess.check_call(
        ["sphinx-build", "-W", "-blinkcheck",
         "-d", str(doctrees), ".", str(htmldir)])
def test_build_docs(tmpdir):
    doctrees = tmpdir.join("doctrees")
    htmldir = tmpdir.join("html")
    subprocess.check_call([
        "sphinx-build", "-W", "-bhtml",
        "-d", str(doctrees), ".", str(htmldir)])
```



- run `tox -e docs` and then you may integrate this environment along with your other environments into Jenkins.

Note that `pytest` is only installed into the `docs` environment and does not need to be in use or installed with any other environment.

### Access package artifacts between Jenkins jobs

In an extension to *Access package artifacts between multiple tox-runs* you can also configure Jenkins jobs to access each others artifacts. `tox` uses the `distshare` directory to access artifacts and in a Jenkins context (detected via existence of the environment variable `HUDSON_URL`); it defaults to `{toxworkdir}/distshare`.

This means that each workspace will have its own `distshare` directory and we need to configure Jenkins to perform artifact copying. The recommend way to do this is to install the [Jenkins Copy Artifact plugin](#) and for each job which “receives” artifacts you add a **Copy artifacts from another project** build step using roughly this configuration:

```
Project-name: name of the other (tox-managed) job you want the artifact from
Artifacts to copy: .tox/dist/*.zip # where tox jobs create artifacts
Target directory: .tox/distshare # where we want it to appear for us
Flatten Directories: CHECK # create no subdir-structure
```

You also need to configure the “other” job to archive artifacts; This is done by checking `Archive the artifacts` and entering:

```
Files to archive: .tox/dist/*.zip
```

So our “other” job will create an `sdist-package` artifact and the “copy-artifacts” plugin will copy it to our `distshare` area. Now everything proceeds as *Access package artifacts between multiple tox-runs* shows it.

So if you are using defaults you can re-use and debug exactly the same `tox.ini` file and make use of automatic sharing of your artifacts between runs or Jenkins jobs.

### Avoiding the “path too long” error with long shebang lines

If you are using Jenkins builds you might run into the issue that `tox` can not call `pip` because the so called “shebang” line is too long. There is a limit of 127 chars on some systems. Probably the best way to fix the problem is to use the new `--workdir` option which tells `tox` to use a specific directory for its virtualenvironments. Set it to some unique enough short path. If somebody is interested to do a PR you could add a new option to `tox` which uses a random directory for storing its `workdir` results and removes it after the `tox` run finishes. This could be used from CI environments where you probably anyway want to recreate everything on new runs.

## Development environment

`Tox` can be used for just preparing different virtual environments required by a project.

This feature can be used by deployment tools when preparing deployed project environments. It can also be used for setting up normalized project development environments and thus help reduce the risk of different team members using mismatched development environments.

Here are some examples illustrating how to set up a project’s development environment using `tox`. For illustration purposes, let us call the development environment `devenv`.

## Example 1: Basic scenario

### Step 1 - Configure the development environment

First, we prepare the tox configuration for our development environment by defining a `[testenv:devenv]` section in the project's `tox.ini` configuration file:

```
[testenv:devenv]
envdir = devenv
basepython = python2.7
usedevelop = True
```

In it we state:

- what directory to locate the environment in,
- what Python executable to use in the environment,
- that our project should be installed into the environment using `setup.py develop`, as opposed to building and installing its source distribution using `setup.py install`.

Actually, we can configure a lot more, and these are only the required settings. For example, we can add the following to our configuration, telling tox not to reuse `commands` or `deps` settings from the base `[testenv]` configuration:

```
commands =
deps =
```

### Step 2 - Create the development environment

Once the `[testenv:devenv]` configuration section has been defined, we create the actual development environment by running the following:

```
tox -e devenv
```

This creates the environment at the path specified by the environment's `envdir` configuration value.

## Example 2: A more complex scenario

Let us say we want our project development environment to:

- be located in the `devenv` directory,
- use Python executable `python2.7`,
- pull packages from `requirements.txt`, located in the same directory as `tox.ini`.

Here is an example configuration for the described scenario:

```
[testenv:devenv]
envdir = devenv
basepython = python2.7
usedevelop = True
deps = -requirements.txt
```

## Platform specification

### Basic multi-platform example

Assuming the following layout:

```
tox.ini      # see below for content
setup.py     # a classic distutils/setuptools setup.py file
```

and the following `tox.ini` content:

```
[tox]
# platform specification support is available since version 2.0
minversion=2.0
envlist=py{27,36}-{mylinux,mymacos,mywindows}

[testenv]
# environment will be skipped if regular expression does not match against the sys.
↳platform string
platform=
    mylinux: linux
    mymacos: darwin
    mywindows: win32

# you can specify dependencies and their versions based on platform filtered
↳envirements
deps=
    mylinux,mymacos: py==1.4.32
    mywindows: py==1.4.30

# upon tox invocation you will be greeted according to your platform
commands=
    mylinux: python -c 'print("Hello, Linus!")'
    mymacos: python -c 'print("Hello, Steve!")'
    mywindows: python -c 'print("Hello, Bill!")'
```

you can invoke `tox` in the directory where your `tox.ini` resides. `tox` creates two `virtualenv` environments with the `python2.7` and `python3.6` interpreters, respectively, and will then run the specified command according to platform you invoke `tox` at.

## tox configuration specification

`tox.ini` files uses the standard `ConfigParser` “ini-style” format. Below you find the specification, but you might want to skim some *tox configuration and usage examples* first and use this page as a reference.

### Tox global settings

List of optional global options:

```
[tox]
minversion=ver      # minimally required tox version
toxworkdir=path    # tox working directory, defaults to {toxindir}/.tox
setupdir=path      # defaults to {toxindir}
distdir=path       # defaults to {toxworkdir}/dist
```

```
distshare=path      # (DEPRECATED) defaults to {homedir}/.tox/distshare
envlist=ENVLIST     # defaults to the list of all environments
skipsdist=BOOL      # defaults to false
```

tox autodetects if it is running in a Jenkins context (by checking for existence of the JENKINS\_URL environment variable) and will first lookup global tox settings in this section:

```
[tox:jenkins]
...           # override [tox] settings for the jenkins context
# note: for jenkins distshare defaults to ``{toxworkdir}/distshare`` (DEPRECATED)
```

### **skip\_missing\_interpreters=BOOL**

New in version 1.7.2.

Setting this to True is equivalent of passing the `--skip-missing-interpreters` command line option, and will force tox to return success even if some of the specified environments were missing. This is useful for some CI systems or running on a developer box, where you might only have a subset of all your supported interpreters installed but don't want to mark the build as failed because of it. As expected, the command line switch always overrides this setting if passed on the invocation. **Default:** False

### **envlist=CSV**

Determining the environment list that tox is to operate on happens in this order (if any is found, no further lookups are made):

- command line option `-eENVLIST`
- environment variable `TOXENV`
- tox.ini file's `envlist`

## Virtualenv test environment settings

Test environments are defined by a:

```
[testenv:NAME]
...
```

section. The NAME will be the name of the virtual environment. Defaults for each setting in this section are looked up in the:

```
[testenv]
...
```

testenvironment default section.

Complete list of settings that you can put into `testenv*` sections:

### **basepython=NAME-OR-PATH**

name or path to a Python interpreter which will be used for creating the virtual environment. **default:** interpreter used for tox invocation.

### **commands=ARGVLIST**

the commands to be called for testing. Each command is defined by one or more lines; a command can have multiple lines if a line ends with the `\` character in which case the subsequent line will be appended (and may contain another `\` character ...). For eventually performing a call to `subprocess.Popen(args, ...)` `args` are determined by splitting the whole command by whitespace. Similar to make recipe lines, any command with a leading `-` will ignore the exit code.

**install\_command=ARGV**

New in version 1.6.

the `install_command` setting is used for installing packages into the virtual environment; both the package under test and its dependencies (defined with `deps`). Must contain the substitution key `{packages}` which will be replaced by the packages to install. You should also accept `{opts}` if you are using `pip` – it will contain index server options such as `--pre` (configured as `pip_pre`) and potentially index-options from the deprecated `indexserver` option.

**default:**

```
pip install {opts} {packages}
```

**list\_dependencies\_command**

New in version 2.4.

the `list_dependencies_command` setting is used for listing the packages installed into the virtual environment.

**default:**

```
pip freeze
```

**ignore\_errors=True|False (default)**

New in version 2.0: If `True`, a non-zero exit code from one command will be ignored and further commands will be executed (which was the default behavior in `tox < 2.0`). If `False` (the default), then a non-zero exit code from one command will abort execution of commands for that environment.

It may be helpful to note that this setting is analogous to the `-i` or `ignore-errors` option of GNU Make. A similar name was chosen to reflect the similarity in function.

Note that in `tox 2.0`, the default behavior of `tox` with respect to treating errors from commands changed. `Tox < 2.0` would ignore errors by default. `Tox >= 2.0` will abort on an error by default, which is safer and more typical of CI and command execution tools, as it doesn't make sense to run tests if installing some prerequisite failed and it doesn't make sense to try to deploy if tests failed.

**pip\_pre=True|False (default)**

New in version 1.9.

If `True`, adds `--pre` to the `opts` passed to `install_command`. If `install_command` uses `pip`, this will cause it to install the latest available pre-release of any dependencies without a specified version. If `False` (the default), `pip` will only install final releases of unpinned dependencies.

Passing the `--pre` command-line option to `tox` will force this to `True` for all testenvs.

Don't set this option if your `install_command` does not use `pip`.

**whitelist\_externals=MULTI-LINE-LIST**

each line specifies a command name (in glob-style pattern format) which can be used in the `commands` section without triggering a “not installed in virtualenv” warning. Example: if you use the `unix make` for running tests you can list `whitelist_externals=make` or `whitelist_externals=/usr/bin/make` if you want more precision. If you don't want `tox` to issue a warning in any case, just use `whitelist_externals=*` which will match all commands (not recommended).

**changedir=path**

change to this working directory when executing the test command. **default:** `{toxiniidir}`

**deps=MULTI-LINE-LIST**

test-specific dependencies - to be installed into the environment prior to project package installation. Each line defines a dependency, which will be passed to the installer command for processing (see `indexserver`). Each line specifies a file, a URL or a package name. You can additionally specify an `indexserver` to use

for installing this dependency but this functionality is deprecated since tox-2.3. All derived dependencies (deps required by the dep) will then be retrieved from the specified indexserver:

```
deps = :myindexserver:pkg
```

(Experimentally introduced in 1.6.1) all installer commands are executed using the `{toxidir}` as the current working directory.

### **platform=REGEX**

New in version 2.0.

A testenv can define a new `platform` setting as a regular expression. If a non-empty expression is defined and does not match against the `sys.platform` string the test environment will be skipped.

### **setenv=MULTI-LINE-LIST**

New in version 0.9.

each line contains a `NAME=VALUE` environment variable setting which will be used for all test command invocations as well as for installing the `sdist` package into a virtual environment.

### **passenv=SPACE-SEPARATED-GLOBNAMES**

New in version 2.0.

A list of wildcard environment variable names which shall be copied from the tox invocation environment to the test environment when executing test commands. If a specified environment variable doesn't exist in the tox invocation environment it is ignored. You can use `*` and `?` to match multiple environment variables with one name.

Some variables are always passed through to ensure the basic functionality of standard library functions or tooling like pip:

- passed through on all platforms: `PATH`, `LANG`, `LANGUAGE`, `LD_LIBRARY_PATH`, `PIP_INDEX_URL`
- Windows:** `SYSTEMDRIVE`, `SYSTEMROOT`, `PATHEXT`, `TEMP`, `TMP` `NUMBER_OF_PROCESSORS`, `USERPROFILE`, `MSYSTEM`
- Others (e.g. UNIX, macOS): `TMPDIR`

You can override these variables with the `setenv` option.

If defined the `TOX_TESTENV_PASSENV` environment variable (in the tox invocation environment) can define additional space-separated variable names that are to be passed down to the test command environment.

Changed in version 2.7.

`PYTHONPATH` will be passed down if explicitly defined. If `PYTHONPATH` exists in the host environment but is **not** declared in `passenv` a warning will be emitted.

### **recreate=True|False (default)**

Always recreate virtual environment if this option is True.

### **downloadcache=path**

**IGNORED** – Since pip-8 has caching by default this option is now ignored. Please remove it from your configs as a future tox version might bark on it.

### **sitepackages=True|False**

Set to `True` if you want to create virtual environments that also have access to globally installed packages.

**default:** False, meaning that virtualenvs will be created without inheriting the global site packages.

### **alwayscopy=True|False**

Set to `True` if you want virtualenv to always copy files rather than symlinking.

**default:** False, meaning that virtualenvs will make use of symbolic links.

**args\_are\_paths=BOOL**

treat positional arguments passed to `tox` as file system paths and - if they exist on the filesystem - rewrite them according to the `changedir`. **default:** True (due to the exists-on-filesystem check it's usually safe to try rewriting).

**envtmpdir=path**

defines a temporary directory for the virtualenv which will be cleared each time before the group of test commands is invoked. **default:** `{envdir}/tmp`

**envlogdir=path**

defines a directory for logging where tox will put logs of tool invocation. **default:** `{envdir}/log`

**indexserver**

New in version 0.9.

(DEPRECATED, will be removed in a future version) Multi-line `name = URL` definitions of python package servers. Dependencies can specify using a specified index server through the `:indexservername:depname pattern`. The default `indexserver` definition determines where unscoped dependencies and the `sdist` install installs from. Example:

```
[tox]
indexserver =
    default = http://mypypi.org
```

will make tox install all dependencies from this PYPI index server (including when installing the project `sdist` package).

**envdir**

New in version 1.5.

User can set specific path for environment. If path would not be absolute it would be treated as relative to `{toxindir}`. **default:** `{toxworkdir}/{envname}`

**usedevelop=BOOL**

New in version 1.6.

Install the current package in development mode with “`setup.py develop`” instead of installing from the `sdist` package. (This uses `pip`'s `-e` option, so should be avoided if you've specified a custom `install_command` that does not support `-e`).

**default:** False

**skip\_install=BOOL**

New in version 1.9.

Do not install the current package. This can be used when you need the virtualenv management but do not want to install the current package into that environment.

**default:** False

**ignore\_outcome=BOOL**

New in version 2.2.

If set to True a failing result of this testenv will not make tox fail, only a warning will be produced.

**default:** False

**extras=MULTI-LINE-LIST**

New in version 2.4.

A list of “extras” to be installed with the `sdist` or `develop` install. For example, `extras = testing` is equivalent to `[testing]` in a `pip install` command.

**description=SINGLE-LINE-TEXT**

a short description of the environment, this will be used to explain the environment to the user upon listing environments for the command line with any level of verbosity higher than zero. **default:** empty string

## Substitutions

Any `key=value` setting in an ini-file can make use of value substitution through the `{...}` string-substitution pattern.

You can escape curly braces with the `\` character if you need them, for example:

```
commands = echo "\{posargs\}" = {posargs}
```

### Globally available substitutions

- {toxindir}** the directory where tox.ini is located
- {toxworkdir}** the directory where virtual environments are created and sub directories for packaging reside.
- {homedir}** the user-home directory path.
- {distdir}** the directory where sdist-packages will be created in
- {distshare}** (DEPRECATED) the directory where sdist-packages will be copied to so that they may be accessed by other processes or tox runs.
- {:}** OS-specific path separator (: os \*nix family, ; on Windows). May be used in *setenv*, when target variable is path variable (e.g. PATH or PYTHONPATH).

### substitutions for virtualenv-related sections

- {envname}** the name of the virtual environment
- {envpython}** path to the virtual Python interpreter
- {envdir}** directory of the virtualenv hierarchy
- {envbindir}** directory where executables are located
- {envsitepackagesdir}** directory where packages are installed. Note that architecture-specific files may appear in a different directory.
- {envtmpdir}** the environment temporary directory
- {envlogdir}** the environment log directory

### environment variable substitutions

If you specify a substitution string like this:

```
{env:KEY}
```

then the value will be retrieved as `os.environ['KEY']` and raise an Error if the environment variable does not exist.



### environment variable substitutions with default values

If you specify a substitution string like this:

```
{env:KEY:DEFAULTVALUE}
```

then the value will be retrieved as `os.environ['KEY']` and replace with `DEFAULTVALUE` if the environment variable does not exist.

If you specify a substitution string like this:

```
{env:KEY:}
```

then the value will be retrieved as `os.environ['KEY']` and replace with an empty string if the environment variable does not exist.

Substitutions can also be nested. In that case they are expanded starting from the innermost expression:

```
{env:KEY:{env:DEFAULT_OF_KEY}}
```

the above example is roughly equivalent to `os.environ.get('KEY', os.environ['DEFAULT_OF_KEY'])`

### substitutions for positional arguments in commands

New in version 1.0.

If you specify a substitution string like this:

```
{posargs:DEFAULTS}
```

then the value will be replaced with positional arguments as provided to the tox command:

```
tox arg1 arg2
```

In this instance, the positional argument portion will be replaced with `arg1 arg2`. If no positional arguments were specified, the value of `DEFAULTS` will be used instead. If `DEFAULTS` contains other substitution strings, such as `{env:*}`, they will be interpreted,

Use a double `--` if you also want to pass options to an underlying test command, for example:

```
tox -- --opt1 ARG1
```

will make the `--opt1 ARG1` appear in all test commands where `[]` or `{posargs}` was specified. By default (see `args_are_paths` setting), tox rewrites each positional argument if it is a relative path and exists on the filesystem to become a path relative to the `changedir` setting.

Previous versions of tox supported the `[.*]` pattern to denote positional arguments with defaults. This format has been deprecated. Use `{posargs:DEFAULTS}` to specify those.

### Substitution for values from other sections

New in version 1.4.

Values from other sections can be referred to via:

```
{[sectionname]valuename}
```

which you can use to avoid repetition of config values. You can put default values in one section and reference them in others to avoid repeating the same values:

```
[base]
deps =
    pytest
    mock
    pytest-xdist

[testenv:dulwich]
deps =
    dulwich
    {[base]deps}

[testenv:mercurial]
deps =
    mercurial
    {[base]deps}
```

## Generating environments, conditional settings

New in version 1.8.

Suppose you want to test your package against python2.6, python2.7 and against several versions of a dependency, say Django 1.5 and Django 1.6. You can accomplish that by writing down 2\*2 = 4 `[testenv:*]` sections and then listing all of them in `envlist`.

However, a better approach looks like this:

```
[tox]
envlist = {py26,py27}-django{15,16}

[testenv]
basepython =
    py26: python2.6
    py27: python2.7
deps =
    pytest
    django15: Django>=1.5,<1.6
    django16: Django>=1.6,<1.7
    py26: unittest2
commands = pytest
```

This uses two new facilities of tox-1.8:

- generative `envlist` declarations where each `envname` consists of environment parts or “factors”
- “factor” specific settings

Let’s go through this step by step.

## Generative envlist

```
envlist = {py26,py27}-django{15,16}
```

This is bash-style syntax and will create  $2 \times 2 = 4$  environment names like this:

```
py26-django15
py26-django16
py27-django15
py27-django16
```

You can still list environments explicitly along with generated ones:

```
envlist = {py26,py27}-django{15,16}, docs, flake
```

**Note:** To help with understanding how the variants will produce section values, you can ask tox to show their expansion with a new option:

```
$ tox -l
py26-django15
py26-django16
py27-django15
py27-django16
docs
flake
```

## Factors and factor-conditional settings

Parts of an environment name delimited by hyphens are called factors and can be used to set values conditionally:

```
basepython =
  py26: python2.6
  py27: python2.7
```

This conditional setting will lead to either `python2.6` or `python2.7` used as base python, e.g. `python2.6` is selected if current environment contains `py26` factor.

In list settings such as `deps` or `commands` you can freely intermix optional lines with unconditional ones:

```
deps =
  pytest
  django15: Django>=1.5,<1.6
  django16: Django>=1.6,<1.7
  py26: unittest2
```

Reading it line by line:

- `pytest` will be included unconditionally,
- `Django>=1.5,<1.6` will be included for environments containing `django15` factor,
- `Django>=1.6,<1.7` similarly depends on `django16` factor,
- `unittest2` will be loaded for Python 2.6 environments.

**Note:** Tox provides good defaults for `basepython` setting, so the above ini-file can be further reduced by omitting the `basepython` setting.

---

### Complex factor conditions

Sometimes you need to specify the same line for several factors or create a special case for a combination of factors. Here is how you do it:

```
[tox]
envlist = py{26,27,33}-django{15,16}-{sqlite,mysql}

[testenv]
deps =
    py33-mysql: PyMySQL      ; use if both py33 and mysql are in an env name
    py26,py27: urllib3      ; use if any of py26 or py27 are in an env name
    py{26,27}-sqlite: mock  ; mocking sqlite in python 2.x
```

Take a look at first `deps` line. It shows how you can special case something for a combination of factors, you just join combining factors with a hyphen. This particular line states that `PyMySQL` will be loaded for python 3.3, `mysql` environments, e.g. `py33-django15-mysql` and `py33-django16-mysql`.

The second line shows how you use same line for several factors - by listing them delimited by commas. It's possible to list not only simple factors, but also their combinations like `py26-sqlite`, `py27-sqlite`.

Finally, factor expressions are expanded the same way as `envlist`, so last example could be rewritten as `py{26,27}-sqlite`.

---

**Note:** Factors don't do substring matching against env name, instead every hyphenated expression is split by `-` and if ALL the factors in an expression are also factors of an env then that condition is considered hold.

For example, environment `py26-mysql`:

- could be matched with expressions `py26`, `py26-mysql`, `mysql-py26`,
  - but not with `py2` or `py26-sql`.
- 

### Other Rules and notes

- `path` specifications: if a specified `path` is a relative path it will be considered as relative to the `toxidir`, the directory where the configuration file resides.

## V2: new tox multi-dimensional, platform-specific configuration

---

**Note:** This is a draft document sketching a to-be-done implementation. It does not fully specify each change yet but should give a good idea of where things are heading. For feedback, mail the `testing-in-python` mailing list or open a pull request on <https://github.com/tox-dev/tox/blob/master/doc/config-v2.txt>

---

**Abstract:** Adding multi-dimensional configuration, platform-specification and multiple installers to `tox.ini`.

---

**Target audience:** Developers using or wanting to use tox for testing their python projects.

## Issues with current tox (1.4) configuration

Tox is used as a tool for creating and managing virtualenv environments and running tests in them. As of tox-1.4 there are some issues frequently coming up with its configuration language:

- there is no way to instruct tox to parametrize testenv specifications other than to list all combinations by specifying a `[testenv:...]` section for each combination. Examples of real life situations arising from this:
  - <https://github.com/tomchristie/django-rest-framework/blob/b001a146d73348af18cfc4c943d87f2f389349c9/tox.ini>
  - <https://bitbucket.org/tabodjango-treebeard/src/93b579395a9c/tox.ini>
- there is no way to have platform specific settings other than to define specific testenvs and invoke tox with a platform-specific testenv list.
- there is no way to specify the platforms against which a project shall successfully run.
- tox always uses pip for installing packages currently. This has several issues:
  - no way to check if installing via `easy_install` works
  - no installs of packages with compiled c-extensions (win32 standard)

## Goals, resolving those issues

This document discusses a possible solution for each of these issues, namely these goals:

- allow to more easily define and run dependency/interpreter variants with testenvs
- allow platform-specific settings
- allow to specify platforms against which tests should run
- allow to run installer-variants (`easy_install` or `pip`, `xxx`)
- try to mimick/re-use bash-style syntax to ease learning curve.

## Example: Generating and selecting variants

Suppose you want to test your package against python2.6, python2.7 and on the windows and linux platforms. Today you would have to write down  $2*2 = 4$  `[testenv:*]` sections and then instruct tox to run a specific list of environments on each platform.

With tox-1.X you can directly specify combinations:

```
# combination syntax gives 2 * 2 = 4 testenv names
#
envlist = {py26,py27}-{win,linux}

[testenv]
deps = pytest
platform =
    win: windows
    linux: linux
```

```
basepython =
    py26: python2.6
    py27: python2.7
commands = pytest
```

Let's go through this step by step:

```
envlist = {py26,py27}-{windows,linux}
```

This is bash-style syntax and will create  $2 \times 2 = 4$  environment names like this:

```
py26-windows
py26-linux
py27-windows
py27-linux
```

Our `[testenv]` uses a new templating style for the `platform` definition:

```
platform=
    windows: windows
    linux: linux
```

These two conditional settings will lead to either `windows` or `linux` as the `platform` string. When the test environment is run, its `platform` string needs to be contained in the string returned from `platform.platform()`. Otherwise the environment will be skipped.

The next configuration item in the `testenv` section deals with the python interpreter:

```
basepython =
    py26: python2.6
    py27: python2.7
```

This defines a python executable, depending on if `py26` or `py27` appears in the environment name.

The last config item is simply the invocation of the test runner:

```
commands = pytest
```

Nothing special here :)

---

**Note:** Tox provides good defaults for `platform` and `basepython` settings, so the above ini-file can be further reduced:

```
[tox]
envlist = {py26,py27}-{win,linux}

[testenv]
deps = pytest
commands = pytest
```

Voila, this multi-dimensional `tox.ini` configuration defines  $2 \times 2 = 4$  environments.

---

## The new “platform” setting

A `testenv` can define a new `platform` setting. If its value is not contained in the string obtained from calling `sys.platform` the environment will be skipped.

## Expanding the `envlist` setting

The new `envlist` setting allows to use `{ }` bash-style expressions. XXX explanation or pointer to bash-docs

## Templating based on environments names

For a given environment name, all lines in a `testenv` section which start with “NAME: ...” will be checked for being part in the environment name. If they are part of it, the remainder will be the new line. If they are not part of it, the whole line will be left out. Parts of an environment name are obtained by `--splitting` it.

Variant specification with `[variant:VARNAME]`

## Showing all expanded sections

To help with understanding how the variants will produce section values, you can ask `tox` to show their expansion with a new option:

```
$ tox -l [XXX output omitted for now]
```

## Making sure your packages installs with `easy_install`

The new “installer” `testenv` setting allows to specify the tool for installation in a given test environment:

```
[testenv]
installer =
    easy: easy_install
    pip: pip
```

If you want to have your package installed with both `easy_install` and `pip`, you can list them in your `envlist` likes this:

```
[tox]
envlist = py[26,27,32]-django[13,14]-[easy,pip]
```

If no installer is specified, `pip` will be used.

## Default settings related to environments names/variants

`tox` comes with predefined settings for certain variants, namely:

- `{easy, pip}` use `easy_install` or `pip` respectively
- `{py24, py25, py26, py27, py31, py32, py33, py34, pypy19}` use the respective `pythonNN` or `PyPy` interpreter
- `{win32, linux, darwin}` defines the according `platform`.

You can use those in your “`envlist`” specification without the need to define them yourself.

## Use more bash-style syntax

tox leverages bash-style syntax if you specify `mintoxversion = 1.4`:

- `$VARNAME` or `${...}` syntax instead of the older `{}` substitution.
- XXX go through `config.txt` and see how it would need to be changed

## Transforming the examples: django-rest

The original `django-rest-framework` `tox.ini` file has 159 lines and a lot of repetition, the new one would +have 20 lines and almost no repetition:

```
[tox]
envlist = {py25,py26,py27}-{django12,django13}{,-example}

[testenv]
deps=
    coverage==3.4
    unittest-xml-reporting==1.2
    Pyyaml==3.10
    django12: django==1.2.4
    django13: django==1.3.1
    # some more deps for running examples
    example: wsgiref==0.1.2
    example: Pygments==1.4
    example: httpplib2==0.6.0
    example: Markdown==2.0.3

commands =
    !example: python setup.py test
    example: python examples/runtests.py
```

Note that `{,-example}` in the `envlist` denotes two values, an empty one and a `example` one. The empty value means that there are no specific settings and thus no need to define a variant name.

## Transforming the examples: django-treebeard

Another `tox.ini` has 233 lines and runs tests against multiple Postgres and Mysql engines. It also performs backend-specific test commands, passing different command line options to the test script. With the new `tox-1.X` we not only can do the same with 32 non-repetitive configuration lines but we also produce 36 specific `testenvs` with specific dependencies and test commands:

```
[tox]
envlist =
    {py24,py25,py26,py27}-{django11,django12,django13}-{nodb,pg,mysql}, docs

[testenv:docs]
changedir = docs
deps =
    Sphinx
    Django
commands =
    make clean
```



```

make html

[testenv]
deps=
    coverage
    pysqlite
    django11: django==1.1.4
    django12: django==1.2.7
    django13: django==1.3.1
    django14: django==1.4
    nodb: pysqlite
    pg: psycopg2
    mysql: MySQL-python

commands =
    nodb: {envpython} runtests.py {posargs}
    pg: {envpython} runtests.py {posargs} \
        --DATABASE_ENGINE=postgresql_psycopg2 \
        --DATABASE_USER=postgres {posargs}
    mysql: {envpython} runtests.py --DATABASE_ENGINE=mysql \
        --DATABASE_USER=root {posargs}

```

## support and contact channels

Getting in contact:

- join the [tox-dev mailing list](#) for tox related questions and development discussions.
- file a [report on the issue tracker](#)
- hang out on the [irc.freenode.net #pylib](#) channel
- fork the [github repository](#) and submit merge/pull requests

## paid professional support

contact holger at [merlinux.eu](#), an association of experienced well-known Python developers.

## Changelog history

### 2.8.2 (2017-10-09)

#466: stop env var leakage if popen failed with resultjson or redirect

### 2.8.1 (2017-09-04)

- **#p599: fix problems with implementation of #515.** Substitutions from other sections were not made anymore if they were not in *envlist*. Thanks to Clark Boylan (@cboylan) for helping to get this fixed (#p597).

## 2.8.0 (2017-09-01)

- **#276: Remove easy\_install from docs (TL;DR: use pip).** Thanks Martin Andryśík (@sifuraz).
- **#301: Expand nested substitutions in tox.ini** Thanks @vlaci. Thanks to Eli Collins (@eli-collins) for creating a reproducer.
- **#315: add -help and -version to helptox-quickstart** Thanks @vlaci.
- **#326: Fix OSError ‘Not a directory’ when creating env on Jython 2.7.0.** Thanks Nick Douma (@LordGaav).
- **#429: Forward MSYSTEM by default on Windows** Thanks Marius Gedminas (@mgedmin) for reporting this.
- **#449: add multi platform example to the docs.** Thanks Aleks Bunin (@sashkab) and @rndr.
- #474: Start using setuptools\_scm for tag based versioning.
- **#484: Renamed py.test to pytest throughout the project** Thanks Slam (@3lnc).
- **#504: With -a: do not show additional environments header if there are none** Thanks @rndr.
- **#515: Don’t require environment variables in test environments where they are not used.** Thanks André Caron (@AndreLouisCaron).
- **#517: Forward NUMBER\_OF\_PROCESSORS by default on Windows to fix multiprocessing.cpu\_count().** Thanks André Caron (@AndreLouisCaron).
- **#518: Forward USERPROFILE by default on Windows.** Thanks André Caron (@AndreLouisCaron).
- **#p528: Fix some of the warnings displayed by pytest 3.1.0.** Thanks Bruno Oliveira (@nicoddemus).
- **#p547: Add regression test for #137** Thanks Martin Andryśík (@sifuraz).
- **#p553: Add an XFAIL test to reproduce upstream bug #203** Thanks Bartolomé Sánchez Salado (@bart-sanchez).
- **#p556: Report more meaningful errors on why virtualenv creation failed** Thanks @vlaci. Also thanks to Igor Sadchenko (@igor-sadchenko) for pointing out a problem with that PR before it hit the masses :)
- **#575: Add announcement doc to end all announcement docs** (using only CHANGELOG and Github issues since 2.5 already)
- **#p580: Do not ignore Sphinx warnings anymore** Thanks Gábor Bernát (@gaborbernat).
- **#585: Expand documentation to explain pass through of flags from deps to pip** (e.g. -requirements.txt, -constraints.txt) Thanks Alexander Loechel (@loechel).
- #588: Run pytest with xfail\_strict and adapt affected tests.

## 2.7.0 (2017-04-02)

- #p450: Stop after the first installdeps and first testenv create hooks succeed. This changes the default behaviour of `tox_testenv_create` and `tox_testenv_install_deps` to not execute other registered hooks when the first hook returns a result that is not `None`. Thanks Anthony Sottile (@asottile).
- #271 and #464: Improve environment information for users.

New command line parameter: `-a` show **all** defined environments - not just the ones defined in (or generated from) `envlist`.

New verbosity settings for `-l` and `-a`: show user defined descriptions of the environments. This also works for generated environments from factors by concatenating factor descriptions into a complete description.

Note that for backwards compatibility with scripts using the output of `-l` it's output remains unchanged.

Thanks Gábor Bernát (@gaborbernat).

- #464: Fix incorrect egg-info location for modified package\_dir in setup.py. Thanks Selim Belhaouane (@selimb).
- #431: Add 'LANGUAGE' to default passed environment variables. Thanks Paweł Adamczak (@pawalad).
- #455: Add a Vagrantfile with a customized Arch Linux box for local testing. Thanks Oliver Bestwalter (@obestwalter).
- #454: Revert #407, empty commands is not treated as an error. Thanks Anthony Sottile (@asottile).
- #446: (infrastructure) Travis CI tests for tox now also run on OS X now. Thanks Jason R. Coombs (@jaraco).

## 2.6.0 (2017-02-04)

- add "alwayscopy" config option to instruct virtualenv to always copy files instead of symlinking. Thanks Igor Duarte Cardoso (@igordcard).
- pass setenv variables to setup.py during a usedevelop install. Thanks Eli Collins (@eli-collins).
- replace all references to testrun.org with readthedocs ones. Thanks Oliver Bestwalter (@obestwalter).
- fix #323 by avoiding virtualenv14 is not used on py32 (although we don't officially support py32). Thanks Jason R. Coombs (@jaraco).
- add Python 3.6 to envlist and CI. Thanks Andrii Soldatenko (@andriisoldatenko).
- fix glob resolution from TOX\_TESTENV\_PASSENV env variable Thanks Allan Feldman (@a-feld).

## 2.5.0 (2016-11-16)

- slightly backward incompatible: fix issue310: the {posargs} substitution now properly preserves the tox command line positional arguments. Positional arguments with spaces are now properly handled. NOTE: if your tox invocation previously used extra quoting for positional arguments to work around issue310, you need to remove the quoting. Example: `tox - "some string" #` has to now be written simply as `tox - "some string"` thanks holger krekel. You can set `minversion = 2.5.0` in the `[tox]` section of `tox.ini` to make sure people using your `tox.ini` use the correct version.
- fix #359: add COMSPEC to default passenv on windows. Thanks @anthrotype.
- add support for py36 and py37 and add py36-dev and py37(nightly) to travis builds of tox. Thanks John Vandenberg.
- fix #348: add py2 and py3 as default environments pointing to "python2" and "python3" basepython executables. Also fix #347 by updating the list of default envs in the tox basic example. Thanks Tobias McNulty.
- make "-h" and "--help-ini" options work even if there is no tox.ini, thanks holger krekel.
- add {;} substitution, which is replaced with os-specific path separator, thanks Lukasz Rogalski.
- fix #305: `downloadcache` test env config is now ignored as pip-8 does caching by default. Thanks holger krekel.
- output from install command in verbose (-vv) mode is now printed to console instead of being redirected to file, thanks Lukasz Rogalski
- fix #399. Make sure {envtmpdir} is created if it doesn't exist at the start of a testenvironment run. Thanks Manuel Jacob.

- fix #316: Lack of commands key in ini file is now treated as an error. Reported virtualenv status is ‘nothing to do’ instead of ‘commands succeeded’, with relevant error message displayed. Thanks Lukasz Rogalski.

### 2.4.1 (2016-10-12)

- fix issue380: properly perform substitution again. Thanks Ian Cordasco.

### 2.4.0 (2016-10-12)

- remove PYTHONPATH from environment during the install phase because a tox-run should not have hidden dependencies and the test commands will also not see a PYTHONPATH. If this causes unforeseen problems it may be reverted in a bugfix release. Thanks Jason R. Coombs.
- fix issue352: prevent a configuration where envdir==toxindir and refine docs to warn people about changing “envdir”. Thanks Oliver Bestwaller and holger krekel.
- fix issue375, fix issue330: warn against tox-setup.py integration as “setup.py test” should really just test with the current interpreter. Thanks Ronny Pfannschmidt.
- fix issue302: allow cross-testenv substitution where we substitute with {x, y} generative syntax. Thanks Andrew Pashkin.
- fix issue212: allow escaping curly brace chars “{” and “}” if you need the chars “{” and “}” to appear in your commands or other ini values. Thanks John Vandenberg.
- addresses issue66: add --workdir option to override where tox stores its “.tox” directory and all of the virtualenv environment. Thanks Danring.
- introduce per-venv list\_dependencies\_command which defaults to “pip freeze” to obtain the list of installed packages. Thanks Ted Shaw, Holger Krekel.
- close issue66: add documentation to jenkins page on how to avoid “too long shebang” lines when calling pip from tox. Note that we can not use “python -m pip install X” by default because the latter adds the CWD and pip will think X is installed if it is there. “pip install X” does not do that.
- new list\_dependencies\_command to influence how tox determines which dependencies are installed in a testenv.
- (experimental) New feature: When a search for a config file fails, tox tries loading setup.cfg with a section prefix of “tox”.
- fix issue275: Introduce hooks tox\_runtest\_pre` and tox\_runtest\_post which run before and after the tests of a venv, respectively. Thanks to Matthew Schinckel and itxaka serrano.
- fix issue317: evaluate minversion before tox config is parsed completely. Thanks Sachi King for the PR.
- added the “extras” environment option to specify the extras to use when doing the sdist or develop install. Contributed by Alex Grönholm.
- use pytest-catchlog instead of pytest-capturelog (latter is not maintained, uses deprecated pytest API)

### 2.3.2 (2016-02-11)

- fix issue314: fix command invocation with .py scripts on windows.
- fix issue279: allow cross-section substitution when the value contains posargs. Thanks Sachi King for the PR.

### 2.3.1 (2015-12-14)

- fix issue294: re-allow cross-section substitution for setenv.

### 2.3.0 (2015-12-09)

- DEPRECATE use of “indexservers” in tox.ini. It complicates the internal code and it is recommended to rather use the devpi system for managing indexes for pip.
- fix issue285: make setenv processing fully lazy to fix regressions of tox-2.2.X and so that we can now have testenv attributes like “basepython” depend on environment variables that are set in a setenv section. Thanks Nelfin for some tests and initial work on a PR.
- allow “#” in commands. This is slightly incompatible with commands sections that used a comment after a “” line continuation. Thanks David Stanek for the PR.
- fix issue289: fix build\_sphinx target, thanks Barry Warsaw.
- fix issue252: allow environment names with special characters. Thanks Julien Castets for initial PR and patience.
- introduce experimental tox\_testenv\_create(venv, action) and tox\_testenv\_install\_deps(venv, action) hooks to allow plugins to do additional work on creation or installing deps. These hooks are experimental mainly because of the involved “venv” and session objects whose current public API is not fully guaranteed.
- internal: push some optional object creation into tests because tox core doesn’t need it.

### 2.2.1 (2015-12-09)

- fix bug where {envdir} substitution could not be used in setenv if that env value is then used in {basepython}. Thanks Florian Bruhin.

### 2.2.0 (2015-11-11)

- fix issue265 and add LD\_LIBRARY\_PATH to passenv on linux by default because otherwise the python interpreter might not start up in certain configurations (redhat software collections). Thanks David Riddle.
- fix issue246: fix regression in config parsing by reordering such that {envbindir} can be used again in tox.ini. Thanks Olli Walsh.
- fix issue99: the {env:...} substitution now properly uses environment settings from the setenv section. Thanks Itxaka Serrano.
- fix issue281: make -force-dep work when urls are present in dependency configs. Thanks Glyph Lefkowitz for reporting.
- fix issue174: add new ignore\_outcome testenv attribute which can be set to True in which case it will produce a warning instead of an error on a failed testenv command outcome. Thanks Rebecka Gulliksson for the PR.
- fix issue280: properly skip missing interpreter if {envsitepackagesdir} is present in commands. Thanks BB:ceridwen

### 2.1.1 (2015-06-23)

- fix platform skipping for detox

- report skipped platforms as skips in the summary

### 2.1.0 (2015-06-19)

- fix issue258, fix issue248, fix issue253: for non-test commands (installation, venv creation) we pass in the full invocation environment.
- remove experimental `--set-home` option which was hardly used and hackily implemented (if people want home-directory isolation we should figure out a better way to do it, possibly through a plugin)
- fix issue259: `passenv` is now a line-list which allows to intersperse comments. Thanks stefano-m.
- allow `envlist` to be a multi-line list, to intersperse comments and have long `envlist` settings split more naturally. Thanks Andre Caron.
- introduce a `TOX_TESTENV_PASSENV` setting which is honored when constructing the set of environment variables for test environments. Thanks Marc Abramowitz for pushing in this direction.

### 2.0.2 (2015-06-03)

- fix issue247: `tox` now passes the `LANG` variable from the `tox` invocation environment to the test environment by default.
- add `SYSTEMDRIVE` into default `passenv` on windows to allow `pip6` to work. Thanks Michael Krause.

### 2.0.1 (2015-05-13)

- fix wheel packaging to properly require `argparse` on `py26`.

### 2.0.0 (2015-05-12)

- (new) introduce environment variable isolation: `tox` now only passes the `PATH` and `PIP_INDEX_URL` variable from the `tox` invocation environment to the test environment and on Windows also `SYSTEMROOT`, `PATHEXT`, `TEMP` and `TMP` whereas on unix additionally `TMPDIR` is passed. If you need to pass through further environment variables you can use the new `passenv` setting, a space-separated list of environment variable names. Each name can make use of `fnmatch`-style glob patterns. All environment variables which exist in the `tox`-invocation environment will be copied to the test environment.
- a new `--help-ini` option shows all possible `testenv` settings and their defaults.
- (new) introduce a way to specify on which platform a `testenvironment` is to execute: the new per-venv “platform” setting allows to specify a regular expression which is matched against `sys.platform`. If `platform` is set and doesn’t match the platform spec in the test environment the test environment is ignored, no setup or tests are attempted.
- (new) add per-venv “ignore\_errors” setting, which defaults to `False`. If `True`, a non-zero exit code from one command will be ignored and further commands will be executed (which was the default behavior in `tox < 2.0`). If `False` (the default), then a non-zero exit code from one command will abort execution of commands for that environment.
- show and store in `json` the version dependency information for each `venv`
- remove the long-deprecated “`distribute`” option as it has no effect these days.
- fix issue233: avoid hanging with `tox-setupuptools` integration example. Thanks `simonb`.

- fix issue120: allow substitution for the commands section. Thanks Volodymyr Vitvitski.
- fix issue235: fix AttributeError with `-installpkg`. Thanks Volodymyr Vitvitski.
- tox has now somewhat pep8 clean code, thanks to Volodymyr Vitvitski.
- fix issue240: allow to specify empty argument list without it being rewritten to `''`. Thanks Daniel Hahler.
- introduce experimental (not much documented yet) plugin system based on pytest's externalized "pluggy" system. See `tox/hooksspecs.py` for the current hooks.
- introduce `parser.add_testenv_attribute()` to register an ini-variable for testenv sections. Can be used from plugins through the `tox_add_option` hook.
- rename internal files – tox offers no external API except for the experimental plugin hooks, use tox internals at your own risk.
- DEPRECATE `distshare` in documentation

### 1.9.2 (2015-03-23)

- backout ability that `-force-dep` substitutes name/versions in requirement files due to various issues. This fixes issue228, fixes issue230, fixes issue231 which popped up with 1.9.1.

### 1.9.1 (2015-03-23)

- use a file instead of a pipe for command output in `--result-json`. Fixes some termination issues with python2.6.
- allow `-force-dep` to override dependencies in `-r` requirements files. Thanks Sontek for the PR.
- fix issue227: use `-m virtualenv` instead of `-mvirtualenv` to make it work with pyrun. Thanks Marc-Andre Lemburg.

### 1.9.0 (2015-02-24)

- fix issue193: Remove `--pre` from the default `install_command`; by default tox will now only install final releases from PyPI for unpinned dependencies. Use `pip_pre = true` in a testenv or the `--pre` command-line option to restore the previous behavior.
- fix issue199: fill `resultlog` structure ahead of `virtualenv` creation
- refine determination if we run from Jenkins, thanks Borge Lanes.
- echo output to stdout when `--report-json` is used
- fix issue11: add a `skip_install` per-testenv setting which prevents the installation of a package. Thanks Julian Krause.
- fix issue124: ignore command exit codes; when a command has a `"-"` prefix, tox will ignore the exit code of that command
- fix issue198: fix broken `envlist` settings, e.g. `{py26,py27}{-lint,}`
- fix issue191: lessen `factor-use` checks

### 1.8.1 (2014-10-24)

- fix issue190: allow setenv to be empty.
- allow escaping curly braces with “””. Thanks Marc Abramowitz for the PR.
- allow “.” names in environment names such that “py27-django1.7” is a valid environment name. Thanks Alex Gaynor and Alex Schepanovski.
- report subprocess exit code when execution fails. Thanks Marius Gedminas.

### 1.8.0 (2014-09-24)

- new multi-dimensional configuration support. Many thanks to Alexander Schepanovski for the complete PR with docs. And to Mike Bayer and others for testing and feedback.
- fix issue148: remove “\_\_PYVENV\_LAUNCHER\_\_” from os.environ when starting subprocesses. Thanks Steven Myint.
- fix issue152: set VIRTUAL\_ENV when running test commands, thanks Florian Ludwig.
- better report if we can’t get version\_info from an interpreter executable. Thanks Floris Bruynooghe.

### 1.7.2 (2014-07-15)

- fix issue150: parse {posargs} more like we used to do it pre 1.7.0. The 1.7.0 behaviour broke a lot of Open-Stack projects. See PR85 and the issue discussions for (far) more details, hopefully resulting in a more refined behaviour in the 1.8 series. And thanks to Clark Boylan for the PR.
- fix issue59: add a config variable skip-missing-interpreters as well as command line option --skip-missing-interpreters which won’t fail the build if Python interpreters listed in tox.ini are missing. Thanks Alexandre Conrad for PR104.
- fix issue164: better traceback info in case of failing test commands. Thanks Marc Abramowitz for PR92.
- support optional env variable substitution, thanks Morgan Fainberg for PR86.
- limit python hashseed to 1024 on Windows to prevent possible memory errors. Thanks March Schlaich for the PR90.

### 1.7.1 (2014-03-28)

- fix issue162: don’t list python 2.5 as compatibility/supported
- fix issue158 and fix issue155: windows/virtualenv properly works now: call virtualenv through “python -m virtualenv” with the same interpreter which invoked tox. Thanks Chris Withers, Ionel Maries Cristian.

### 1.7.0 (2014-01-29)

- don’t lookup “pip-script” anymore but rather just “pip” on windows as this is a pip implementation detail and changed with pip-1.5. It might mean that tox-1.7 is not able to install a different pip version into a virtualenv anymore.
- drop Python2.5 compatibility because it became too hard due to the setuptools-2.0 dropping support. tox now has no support for creating python2.5 based environments anymore and all internal special-handling has been removed.



- merged PR81: new option `--force-dep` which allows to override tox.ini specified dependencies in setup tools-style. For example `--force-dep 'django<1.6'` will make sure that any environment using “django” as a dependency will get the latest 1.5 release. Thanks Bruno Oliveria for the complete PR.
- merged PR125: tox now sets “PYTHONHASHSEED” to a random value and offers a “--hashseed” option to repeat a test run with a specific seed. You can also use `--hashseed=noset` to instruct tox to leave the value alone. Thanks Chris Jerdonek for all the work behind this.
- fix issue132: removing `zip_safe` setting (so it defaults to false) to allow installation of tox via `easy_install/eggs`. Thanks Jenisys.
- fix issue126: depend on `virtualenv>=1.11.2` so that we can rely (hopefully) on a pip version which supports `--pre`. (tox by default uses `--pre`). also merged in PR84 so that we now call “virtualenv” directly instead of looking up interpreters. Thanks Ionel Marius Cristian. This also fixes issue140.
- fix issue130: you can now set `install_command=easy_install {opts} {packages}` and expect it to work for repeated tox runs (previously it only worked when always recreating). Thanks jenisys for precise reporting.
- fix issue129: tox now uses `Popen(..., universal_newlines=True)` to force creation of unicode stdout/stderr streams. fixes a problem on specific platform configs when creating virtualenvs with Python3.3. Thanks Jorgen Schäfer for investigation and solution sketch.
- fix issue128: enable full substitution in `install_command`, thanks for the PR to Ronald Evers
- rework and simplify “commands” parsing and in particular `posargs` substitutions to avoid various win32/posix related quoting issues.
- make sure that the `--installpkg` option trumps any `usedevelop` settings in tox.ini or
- introduce `--no-network` to tox’s own test suite to skip tests requiring networks
- introduce `--sitepackages` to force `sitepackages=True` in all environments.
- fix issue105 – don’t depend on an existing HOME directory from tox tests.

### 1.6.1 (2013-09-04)

- fix issue119: `{envsitepackagesdir}` is now correctly computed and has a better test to prevent regression.
- fix issue116: make 1.6 introduced behaviour of changing to a per-env HOME directory during install activities dependent on “--set-home” for now. Should re-establish the old behaviour when no option is given.
- fix issue118: correctly have two tests use `realpath()`. Thanks Barry Warsaw.
- fix test runs on environments without a home directory (in this case we use `toxindir` as the `homedir`)
- fix issue117: python2.5 fix: don’t use `--insecure` option because its very existence depends on presence of “ssl”. If you want to support python2.5/pip1.3.1 based test environments you need to install ssl and/or use `PIP_INSECURE=1` through `setenv` section.
- fix issue102: change to `{toxindir}` when installing dependencies. this allows to use relative path like in “-requirements.txt”.

### 1.6.0 (2013-08-15)

- fix issue35: add new EXPERIMENTAL “`install_command`” testenv-option to configure the installation command with options for `dep/pkg` install. Thanks Carl Meyer for the PR and docs.
- fix issue91: python2.5 support by vendoring the `virtualenv-1.9.1` script and forcing `pip<1.4`. Also the default [py25] environment modifies the default `install_command` (new config option) to use pip without the “--pre”

option which was introduced with pip-1.4 and is now required if you want to install non-stable releases. (tox defaults to install with “-pre” everywhere).

- during installation of dependencies HOME is now set to a pseudo location (`{envtmpdir}/pseudo-home`). If an index url was specified a `.pydistutils.cfg` file will be written with an `index_url` setting so that packages defining `setup_requires` dependencies will not silently use your HOME-directory settings or <https://pypi.python.org>.
- fix issue1: empty setup files are properly detected, thanks Anthon van der Neuth
- remove `toxbootstrap.py` for now because it is broken.
- fix issue109 and fix issue111: multiple “-e” options are now combined (previously the last one would win). Thanks Anthon van der Neut.
- add `-result-json` option to write out detailed per-venv information into a json report file to be used by upstream tools.
- add new config options `usedevelop` and `skipsdist` as well as a command line option `--develop` to install the package-under-test in develop mode. thanks Monty Taylor for the PR.
- always unset `PYTHONDONTWRITEBYTE` because newer `setuptools` doesn't like it
- if a `HOMEDIR` cannot be determined, use the `toxinidir`.
- refactor interpreter information detection to live in new `tox/interpreters.py` file, tests in `tests/test_interpreters.py`.

### 1.5.0 (2013-06-22)

- fix issue104: use `setuptools` by default, instead of `distribute`, now that `setuptools` has `distribute` merged.
- make sure test commands are searched first in the `virtualenv`
- re-fix issue2 - add `whitelist_externals` to be used in `[testenv*]` sections, allowing to avoid warnings for commands such as `make`, used from the `commands` value.
- fix issue97 - allow substitutions to reference from other sections (thanks Krisztian Fekete)
- fix issue92 - fix `{envsitepackagesdir}` to actually work again
- show (test) command that is being executed, thanks Lukasz Balcerzak
- re-license tox to MIT license
- depend on `virtualenv-1.9.1`
- rename `README.txt` to `README.rst` to make bitbucket happier

### 1.4.3 (2013-02-28)

- use `pip-script.py` instead of `pip.exe` on win32 to avoid the lock exe file on execution issue (thanks Philip Thiem)
- introduce `-ll-listenv` option to list configured environments (thanks Lukasz Balcerzak)
- fix `downloadcache` determination to work according to docs: Only make pip use a download cache if `PIP_DOWNLOAD_CACHE` or a `downloadcache=PATH` `testenv` setting is present. (The `ENV` setting takes precedence)
- fix issue84 - pypy on windows creates a `bin` not a `scripts` `venv` directory (thanks Lukasz Balcerzak)
- experimentally introduce `-installpkg=PATH` option to install a package rather than create/install an `sdist` package. This will still require and use `tox.ini` and tests from the current working dir (and not from the remote package).

- substitute {envsitepackagesdir} with the package installation directory (closes #72) (thanks g2p)
- issue #70 remove PYTHONDONTWRITEBYTECODE workaround now that virtualenv behaves properly (thanks g2p)
- merged tox-quickstart command, contributed by Marc Abramowitz, which generates a default tox.ini after asking a few questions
- fix #48 - win32 detection of pypy and other interpreters that are on PATH (thanks Gustavo Picon)
- fix grouping of index servers, it is now done by name instead of indexserver url, allowing to use it to separate dependencies into groups even if using the same default indexserver.
- look for “tox.ini” files in parent dirs of current dir (closes #34)
- the “py” environment now by default uses the current interpreter (sys.executable) make tox’ own setup.py test execute tests with it (closes #46)
- change tests to not rely on os.path.expanduser (closes #60), also make mock session return args[1:] for more precise checking (closes #61) thanks to Barry Warsaw for both.

### 1.4.2 (2012-07-20)

- fix some tests which fail if /tmp is a symlink to some other place
- “python setup.py test” now runs tox tests via tox :) also added an example on how to do it for your project.

### 1.4.1 (2012-07-03)

- fix issue41 better quoting on windows - you can now use “<” and “>” in deps specifications, thanks Chris Withers for reporting

## 1.4 (2012-06-13)

- fix issue26 - no warnings on absolute or relative specified paths for commands
- fix issue33 - commentchars are ignored in key-value settings allowing for specifying commands like: python -c “import sys ; print sys” which would formerly raise irritating errors because the “;” was considered a comment
- tweak and improve reporting
- refactor reporting and virtualenv manipulation to be more accessible from 3rd party tools
- support value substitution from other sections with the {[section]key} syntax
- fix issue29 - correctly point to pytest explanation for importing modules fully qualified
- fix issue32 - use --system-site-packages and don’t pass --no-site-packages
- add python3.3 to the default env list, so early adopters can test
- drop python2.4 support (you can still have your tests run on
- fix the links/checkout howtos in the docs python-2.4, just tox itself requires 2.5 or higher.

### 1.3 2011-12-21

- fix: allow to specify wildcard filesystem paths when specifying dependencies such that tox searches for the highest version
- fix issue issue21: clear PIP\_REQUIRES\_VIRTUALENV which avoids pip installing to the wrong environment, thanks to bb's streeter
- make the install step honour a testenv's setenv setting (thanks Ralf Schmitt)

### 1.2 2011-11-10

- remove the virtualenv.py that was distributed with tox and depend on >=virtualenv-1.6.4 (possible now since the latter fixes a few bugs that the inlining tried to work around)
- fix issue10: work around UnicodeDecodeError when invoking pip (thanks Marc Abramowitz)
- fix a problem with parsing {posargs} in tox commands (spotted by goodwill)
- fix the warning check for commands to be installed in testenvironment (thanks Michael Foord for reporting)

### 1.1 (2011-07-08)

- fix issue5 - don't require argparse for python versions that have it
- fix issue6 - recreate virtualenv if installing dependencies failed
- fix issue3 - fix example on frontpage
- fix issue2 - warn if a test command does not come from the test environment
- fixed/enhanced: except for initial install always call "-U --no-deps" for installing the sdist package to ensure that a package gets upgraded even if its version number did not change. (reported on TIP mailing list and IRC)
- inline virtualenv.py (1.6.1) script to avoid a number of issues, particularly failing to install python3 environments from a python2 virtualenv installation.
- rework and enhance docs for display on readthedocs.org

### 1.0

- move repository and toxbootstrap links to <http://bitbucket.org/hpk42/tox>
- fix issue7: introduce a "minversion" directive such that tox bails out if it does not have the correct version.
- fix issue24: introduce a way to set environment variables for for test commands (thanks Chris Rose)
- fix issue22: require virtualenv-1.6.1, obsoleting virtualenv5 (thanks Jannis Leidel) and making things work with pypy-1.5 and python3 more seamlessly
- toxbootstrap.py (used by jenkins build slaves) now follows the latest release of virtualenv
- fix issue20: document format of URLs for specifying dependencies
- fix issue19: substitute Hudson for Jenkins everywhere following the renaming of the project. NOTE: if you used the special [tox:hudson] section it will now need to be named [tox:jenkins].
- fix issue 23 / apply some ReST fixes
- change the positional argument specifier to use {posargs:} syntax and fix issues #15 and #10 by refining the argument parsing method (Chris Rose)

- remove use of inipkg lazy importing logic - the namespace/imports are anyway very small with tox.
- fix a fspath related assertion to work with debian installs which uses symlinks
- show path of the underlying virtualenv invocation and bootstrap virtualenv.py into a working subdir
- added a CONTRIBUTORS file

## 0.9

- fix pip-installation mixups by always unsetting PIP\_RESPECT\_VIRTUALENV (thanks Armin Ronacher)
- issue1: Add a toxbootstrap.py script for tox, thanks to Sridhar Ratnakumar
- added support for working with different and multiple PyPI indexeservers.
- new option: -rl--recreate to force recreation of virtualenv
- depend on py>=1.4.0 which does not contain or install the py.test anymore which is now a separate distribution “pytest”.
- show logfile content if there is an error (makes CI output more readable)

## 0.8

- work around a virtualenv limitation which crashes if PYTHONDONTWRITEBYTECODE is set.
- run pip/easy installs from the environment log directory, avoids naming clashes between env names and dependencies (thanks ronny)
- require a more recent version of py lib
- refactor and refine config detection to work from a single file and to detect the case where a python installation overwrote an old one and resulted in a new executable. This invalidates the existing virtualenvironment now.
- change all internal source to strip trailing whitespaces

## 0.7

- use virtualenv5 (my own fork of virtualenv3) for now to create python3 environments, fixes a couple of issues and makes tox more likely to work with Python3 (on non-windows environments)
- add sitepackages option for testenv sections so that environments can be created with access to globals (default is not to have access, i.e. create environments with --no-site-packages.
- addressing issue4: always prepend venv-path to PATH variable when calling subprocesses
- fix issue2: exit with proper non-zero return code if there were errors or test failures.
- added unittest2 examples contributed by Michael Foord
- only allow ‘True’ or ‘False’ for boolean config values (lowercase / uppercase is irrelevant)
- recreate virtualenv on changed configurations

## 0.6

- fix OSX related bugs that could cause the caller's environment to get screwed (sorry). tox was using the same file as virtualenv for tracking the Python executable dependency and there also was confusion wrt links. this should be fixed now.
- fix long description, thanks Michael Foord

## 0.5

- initial release

## tox plugins

New in version 2.0.

With tox-2.0 a few aspects of tox running can be experimentally modified by writing hook functions. The list of available hook function is to grow over time on a per-need basis.

### writing a setuptools entrypoints plugin

If you have a `tox_MYPLUGIN.py` module you could use the following rough `setup.py` to make it into a package which you can upload to the Python packaging index:

```
# content of setup.py
from setuptools import setup

if __name__ == "__main__":
    setup(
        name='tox-MYPLUGIN',
        description='tox plugin decription',
        license="MIT license",
        version='0.1',
        py_modules=['tox_MYPLUGIN'],
        entry_points={'tox': ['MYPLUGIN = tox_MYPLUGIN']},
        install_requires=['tox>=2.0'],
    )
```

If installed, the `entry_points` part will make tox see and integrate your plugin during startup.

You can install the plugin for development (“in-place”) via:

```
pip install -e .
```

and later publish it via something like:

```
python setup.py sdist register upload
```

### Writing hook implementations

A plugin module defines one or more hook implementation functions by decorating them with tox's `hookimpl` marker:

```

from tox import hookimpl

@hookimpl
def tox_addoption(parser):
    # add your own command line options

@hookimpl
def tox_configure(config):
    # post process tox configuration after cmdline/ini file have
    # been parsed

```

If you put this into a module and make it pypi-installable with the `tox` entry point you'll get your code executed as part of a tox run.

## tox hook specifications and related API

Hook specifications for tox.

`tox.hookspeccs.tox_addoption` (*parser*)  
add command line options to the argparse-style parser object.

`tox.hookspeccs.tox_configure` (*config*)  
called after command line options have been parsed and the ini-file has been read. Please be aware that the config object layout may change as its API was not designed yet wrt to providing stability (it was an internal thing purely before tox-2.0).

`tox.hookspeccs.tox_get_python_executable` (*envconfig*)  
return a python executable for the given python base name. The first plugin/hook which returns an executable path will determine it.  
  
*envconfig* is the testenv configuration which contains per-testenv configuration, notably the `.envname` and `.basepython` setting.

`tox.hookspeccs.tox_runttest` (*venv, redirect*)  
[experimental] run the tests for this venv.

---

**Note:** This hook uses `firstresult=True` (see [pluggy](#)) – hooks implementing this will be run until one returns non-None.

---

`tox.hookspeccs.tox_runttest_post` (*venv*)  
[experimental] perform arbitrary action after running tests for this venv.  
  
This could be used to have per-venv test reporting of pass/fail status.

`tox.hookspeccs.tox_runttest_pre` (*venv*)  
[experimental] perform arbitrary action before running tests for this venv.  
  
This could be used to indicate that tests for a given venv have started, for instance.

`tox.hookspeccs.tox_testenv_create` (*venv, action*)  
[experimental] perform creation action for this venv.

Some example usage:

- To *add* behavior but still use tox's implementation to set up a virtualenv, implement this hook but do not return a value (or explicitly return `None`).

- To *override* tox’s virtualenv creation, implement this hook and return a non-None value.

---

**Note:** This api is experimental due to the unstable api of `tox.venv.VirtualEnv`.

---

---

**Note:** This hook uses `firstresult=True` (see [pluggy](#)) – hooks implementing this will be run until one returns non-None.

---

`tox.hookspecs.tox_testenv_install_deps` (*venv, action*)  
[experimental] perform install dependencies action for this venv.

Some example usage:

- To *add* behavior but still use tox’s implementation to install dependencies, implement this hook but do not return a value (or explicitly return `None`). One use-case may be to install (or ensure) non-python dependencies such as debian packages.
- To *override* tox’s installation of dependencies, implement this hook and return a non-None value. One use-case may be to install via a different installation tool such as [pip-accel](#) or [pip-faster](#).

---

**Note:** This api is experimental due to the unstable api of `tox.venv.VirtualEnv`.

---

---

**Note:** This hook uses `firstresult=True` (see [pluggy](#)) – hooks implementing this will be run until one returns non-None.

---

**class** `tox.config.Parser`  
command line and ini-parser control object.

**add\_argument** (*\*args, \*\*kwargs*)  
add argument to command line parser. This takes the same arguments that `argparse.ArgumentParser.add_argument`.

**add\_testenv\_attribute** (*name, type, help, default=None, postprocess=None*)  
add an ini-file variable for “testenv” section.

Types are specified as strings like “bool”, “line-list”, “string”, “argv”, “path”, “argvlist”.

The `postprocess` function will be called for each testenv like `postprocess(testenv_config=testenv_config, value=value)` where `value` is the value as read from the ini (or the default value) and `testenv_config` is a `tox.config.TestenvConfig` instance which will receive all ini-variables as object attributes.

Any `postprocess` function must return a value which will then be set as the final value in the testenv section.

**add\_testenv\_attribute\_obj** (*obj*)  
add an ini-file variable as an object.

This works as the `add_testenv_attribute` function but expects “name”, “type”, “help”, and “post-process” attributes on the object.

**class** `tox.config.Config`  
Global Tox config object.

**envconfigs = None**  
dictionary containing envname to envconfig mappings



**option = None**

option namespace containing all parsed command line options

**class** `tox.config.TestenvConfig`

Testenv Configuration object. In addition to some core attributes/properties this config object holds all per-testenv ini attributes as attributes, see “tox –help-ini” for an overview.

**config = None**

global tox config object

**envname = None**

test environment name

**envpython**

path to python executable.

**factors = None**

set of factors

**get\_envbindir ()**

path to directory where scripts/binaries reside.

**get\_envpython ()**

path to python/jython executable.

**get\_envsitepackagesdir ()**

return sitepackagesdir of the virtualenv environment. (only available during execution, not parsing)

**missing\_subs = None**

Holds substitutions that could not be resolved.

Pre 2.8.1 missing substitutions crashed with a ConfigError although this would not be a problem if the env is not part of the current testrun. So we need to remember this and check later when the testenv is actually run and crash only then.

**python\_info**

return sitepackagesdir of the virtualenv environment.

**class** `tox.venv.VirtualEnv`

**getcommandpath** (*name*, *venv=True*, *cwd=None*)

Return absolute path (str or localpath) for specified command name.

- If it’s a local path we will rewrite it as as a relative path.
- If venv is True we will check if the command is coming from the venv or is whitelisted to come from external.

**name**

test environment name.

**path**

Path to environment base dir.

**update** (*action*)

return status string for updating actual venv to match configuration. if status string is empty, all is ok.

**class** `tox.session.Session`

(unstable API). the session object that ties together configuration, reporting, venv creation, testing.

**get\_installpkg\_path ()**

**Returns** Path to the distribution

**Return type** `py.path.local`

**getvenv** (*name*)

return a VirtualEnv controller object for the 'name' env.

**installpkg** (*venv, path*)

Install package in the specified virtual environment.

:param `tox.config.VenvConfig`: Destination environment :param `str path`: Path to the distribution package. :return: True if package installed otherwise False. :rtype: `bool`

## Writing a json result file

You can instruct tox to write a json-report file via:

```
tox --result-json=PATH
```

This will create a json-formatted result file using this schema:

```
{
  "testenvs": {
    "py27": {
      "python": {
        "executable": "/home/hpk/p/tox/.tox/py27/bin/python",
        "version": "2.7.3 (default, Aug 1 2012, 05:14:39) \n[GCC 4.6.3]",
        "version_info": [ 2, 7, 3, "final", 0 ]
      },
      "test": [
        {
          "output": "...",
          "command": [
            "/home/hpk/p/tox/.tox/py27/bin/pytest",
            "--instafail",
            "--junitxml=/home/hpk/p/tox/.tox/py27/log/junit-py27.xml",
            "tests/test_config.py"
          ],
          "retcode": "0"
        }
      ],
      "setup": []
    }
  },
  "platform": "linux2",
  "installpkg": {
    "basename": "tox-1.6.0.dev1.zip",
    "sha256": "b6982dde5789a167c4c35af0d34ef72176d0575955f5331ad04aee9f23af4326",
    "md5": "27ead99fd7fa39ee7614cede6bf175a6"
  },
  "toxversion": "1.6.0.dev1",
  "reportversion": "1"
}
```

## tox 0.5: a generic virtualenv and test management tool for Python

I have been talking about with various people in the last year and am happy to now announce the first release of `tox`. It aims to automate tedious Python related test activities driven from a simple `tox.ini` file, including:

- creation and management of different virtualenv environments
- installing your package into each of them
- running your test tool of choice (including e.g. running sphinx checks)
- testing packages against each other without needing to upload to PyPI

`tox` runs well on Python2.4 up until Python3.1 and integrates well with Continuous Integration servers Jenkins. There are many real-life examples and a good chunk of docs. Read it up on

<http://codespeak.net/tox>

and please report any issues. This is a fresh project and i'd like to drive further improvements from real world needs.

best,

holger krekel

## tox 1.0: the rapid multi-python test automatizer

I am happy to announce `tox 1.0`, mostly a stabilization and streamlined release. `TOX` automates tedious test activities driven from a simple `tox.ini` file, including:

- creation and management of different virtualenv environments with different Python interpreters
- packaging and installing your package into each of them
- running your test tool of choice, be it nose, py.test or unittest2 or other tools such as “sphinx” doc checks
- testing dev packages against each other without needing to upload to PyPI

Docs and examples are at:

<http://tox.readthedocs.org>

Installation:

```
pip install -U tox
```

Note that code hosting and issue tracking has moved from Google to Bitbucket:

<https://bitbucket.org/hpk42/tox>

The 1.0 release includes contributions and is based on feedback and work from Chris Rose, Ronny Pfannschmidt, Jannis Leidel, Jakob Kaplan-Moss, Sridhar Ratnakumar, Carl Meyer and others. Many thanks!

best, Holger Krekel

## CHANGES

- fix issue24: introduce a way to set environment variables for for test commands (thanks Chris Rose)
- fix issue22: require virtualenv-1.6.1, obsoleting virtualenv5 (thanks Jannis Leidel) and making things work with pypy-1.5 and python3 more seamlessly
- toxbootstrap.py (used by jenkins build slaves) now follows the latest release of virtualenv

- fix issue20: document format of URLs for specifying dependencies
- fix issue19: substitute Hudson for Jenkins everywhere following the renaming of the project. NOTE: if you used the special [tox:hudson] section it will now need to be named [tox:jenkins].
- fix issue 23 / apply some ReST fixes
- change the positional argument specifier to use {posargs:} syntax and fix issues #15 and #10 by refining the argument parsing method (Chris Rose)
- remove use of inipkg lazy importing logic - the namespace/imports are anyway very small with tox.
- fix a fspath related assertion to work with debian installs which uses symlinks
- show path of the underlying virtualenv invocation and bootstrap virtualenv.py into a working subdir
- added a CONTRIBUTORS file

## tox 1.1: the rapid multi-python test automatizer

I am happy to announce tox 1.1, a bug fix release easing some common workflows. TOX automates tedious test activities driven from a simple `tox.ini` file, including:

- creation and management of different virtualenv environments with different Python interpreters
- packaging and installing your package into each of them
- running your test tool of choice, be it nose, py.test or unittest2 or other tools such as “sphinx” doc checks
- testing dev packages against each other without needing to upload to PyPI

It works well on virtually all Python interpreters that support virtualenv.

Docs and examples are at:

<http://tox.readthedocs.org>

Installation:

```
pip install -U tox
```

Note that code hosting and issue tracking has moved from Google to Bitbucket:

<https://bitbucket.org/hpk42/tox>

The 1.0 release includes contributions and is based on feedback and work from Chris Rose, Ronny Pfannschmidt, Jannis Leidel, Jakob Kaplan-Moss, Sridhar Ratnakumar, Carl Meyer and others. Many thanks!

best, Holger Krekel

## CHANGES

- fix issue5 - don't require argparse for python versions that have it
- fix issue6 - recreate virtualenv if installing dependencies failed
- fix issue3 - fix example on frontpage
- fix issue2 - warn if a test command does not come from the test environment
- fixed/enhanced: except for initial install always call “-U --no-deps” for installing the sdist package to ensure that a package gets upgraded even if its version number did not change. (reported on TIP mailing list and IRC)

- inline `virtualenv.py` (1.6.1) script to avoid a number of issues, particularly failing to install python3 environments from a python2 `virtualenv` installation.

## tox 1.2: the virtualenv-based test run automatizer

I am happy to announce tox 1.2, now using and depending on the latest `virtualenv` code and containing some bug fixes. TOX automates tedious test activities driven from a simple `tox.ini` file, including:

- creation and management of different `virtualenv` environments with different Python interpreters
- packaging and installing your package into each of them
- running your test tool of choice, be it nose, `py.test` or `unittest2` or other tools such as “sphinx” doc checks
- testing dev packages against each other without needing to upload to PyPI

It works well on virtually all Python interpreters that support `virtualenv`.

Docs and examples are at:

<http://tox.testrun.org/>

Installation:

```
pip install -U tox
```

code hosting and issue tracking on bitbucket:

<https://bitbucket.org/hpk42/tox>

best, Holger Krekel

### 1.2 compared to 1.1

- remove the `virtualenv.py` that was distributed with tox and depend on `virtualenv-1.6.4` (possible now since the latter fixes a few bugs that the inling tried to work around)
- fix issue10: work around `UnicodeDecodeError` when invoking pip (thanks Marc Abramowitz)
- fix a problem with parsing `{posargs}` in tox commands (spotted by goodwill)
- fix the warning check for commands to be installed in testenvironment (thanks Michael Foord for reporting)

## tox 1.3: the virtualenv-based test run automatizer

I am happy to announce tox 1.3, containing a few improvements over 1.2. TOX automates tedious test activities driven from a simple `tox.ini` file, including:

- creation and management of different `virtualenv` environments with different Python interpreters
- packaging and installing your package into each of them
- running your test tool of choice, be it nose, `py.test` or `unittest2` or other tools such as “sphinx” doc checks
- testing dev packages against each other without needing to upload to PyPI

Docs and examples are at:

<http://tox.testrun.org/>

Installation:

```
pip install -U tox
```

code hosting and issue tracking on bitbucket:

<https://bitbucket.org/hpk42/tox>

best, Holger Krekel

## 1.3

- fix: allow to specify wildcard filesystem paths when specifying dependencies such that tox searches for the highest version
- fix issue issue21: clear PIP\_REQUIRES\_VIRTUALENV which avoids pip installing to the wrong environment, thanks to bb's streeter
- make the install step honour a testenv's setenv setting (thanks Ralf Schmitt)

## tox 1.4: the virtualenv-based test run automatizer

I am happy to announce tox 1.4 which brings:

- improvements with configuration file syntax, now allowing re-using selected settings across config file sections. see <http://testrun.org/tox/latest/config.html#substitution-for-values-from-other-sections>
- terminal reporting was simplified and streamlined. Now with `verbosity==0` (the default), less information will be shown and you can use one or multiple “-v” options to increase verbosity.
- internal re-organisation so that the separately released “detox” tool can reuse tox code to implement a fully distributed tox run.

More documentation:

<http://tox.testrun.org/>

Installation:

```
pip install -U tox
```

code hosting and issue tracking on bitbucket:

<https://bitbucket.org/hpk42/tox>

## What is tox?

tox standardizes and automates tedious test activities driven from a simple `tox.ini` file, including:

- creation and management of different virtualenv environments with different Python interpreters
- packaging and installing your package into each of them
- running your test tool of choice, be it nose, py.test or unittest2 or other tools such as “sphinx” doc checks
- testing dev packages against each other without needing to upload to PyPI

best, Holger Krekel

## 1.4

- fix issue26 - no warnings on absolute or relative specified paths for commands
- fix issue33 - commentchars are ignored in key-value settings allowing for specifying commands like: `python -c "import sys ; print sys"` which would formerly raise irritating errors because the ";" was considered a comment
- tweak and improve reporting
- refactor reporting and virtualenv manipulation to be more accessible from 3rd party tools
- support value substitution from other sections with the `{[section]key}` syntax
- fix issue29 - correctly point to pytest explanation for importing modules fully qualified
- fix issue32 - use `--system-site-packages` and don't pass `--no-site-packages`
- add python3.3 to the default env list, so early adopters can test
- drop python2.4 support (you can still have your tests run on python-2.4, just tox itself requires 2.5 or higher).

### tox 1.4.3: the Python virtualenv-based testing automatizer

tox 1.4.3 fixes some bugs and introduces a new script and two new options:

- “tox-quickstart” - run this script, answer a few questions, and get a tox.ini created for you (thanks Marc Abramowitz)
- “tox -l” lists configured environment names (thanks Lukasz Balcerzak)
- (experimental) “--installpkg=localpath” option which will skip the sdist-creation of a package and instead install the given localpath package.
- use pip-script.py instead of pip.exe on win32 to avoid windows locking the .exe

Note that the sister project “detox” should continue to work - it’s a separately released project which drives tox test runs on multiple CPUs in parallel.

More documentation:

<http://tox.testrun.org/>

Installation:

```
pip install -U tox
```

repository hosting and issue tracking on bitbucket:

<https://bitbucket.org/hpk42/tox>

### What is tox?

tox standardizes and automates tedious python driven test activities driven from a simple `tox.ini` file, including:

- creation and management of different virtualenv environments with different Python interpreters
- packaging and installing your package into each of them
- running your test tool of choice, be it nose, py.test or unittest2 or other tools such as “sphinx” doc checks
- testing dev packages against each other without needing to upload to PyPI

best, Holger Krekel

## CHANGELOG

### 1.4.3 (compared to 1.4.2)

- introduce `-l--listenv` option to list configured environments (thanks Lukasz Balcerzak)
- fix `downloadcache` determination to work according to docs: Only make `pip` use a download cache if `PIP_DOWNLOAD_CACHE` or a `downloadcache=PATH` `testenv` setting is present. (The `ENV` setting takes precedence)
- fix issue84 - `pypy` on windows creates a `bin` not a `scripts` `venv` directory (thanks Lukasz Balcerzak)
- experimentally introduce `--installpkg=PATH` option to install a package rather than create/install an `sdist` package. This will still require and use `tox.ini` and tests from the current working dir (and not from the remote package).
- substitute `{envsitepackagesdir}` with the package installation directory (closes #72) (thanks g2p)
- issue #70 remove `PYTHONDONTWRITEBYTECODE` workaround now that `virtualenv` behaves properly (thanks g2p)
- merged `tox-quickstart` command, contributed by Marc Abramowitz, which generates a default `tox.ini` after asking a few questions
- fix #48 - win32 detection of `pypy` and other interpreters that are on `PATH` (thanks Gustavo Picon)
- fix grouping of index servers, it is now done by name instead of `indexserver` url, allowing to use it to separate dependencies into groups even if using the same default `indexserver`.
- look for “`tox.ini`” files in parent dirs of current dir (closes #34)
- the “`py`” environment now by default uses the current interpreter (`sys.executable`) make `tox`’ own `setup.py` test execute tests with it (closes #46)
- change tests to not rely on `os.path.expanduser` (closes #60), also make `mock` session return `args[1:]` for more precise checking (closes #61) thanks to Barry Warszaw for both.

## tox 1.8: Generative/combinatorial environments specs

I am happy to announce `tox 1.8` which implements parametrized environments.

See <https://tox.testrun.org/latest/config.html#generating-environments-conditional-settings> for examples and the new backward compatible syntax in your `tox.ini` file.

Many thanks to Alexander Schepanovski for implementing and refining it based on the specification draft.

More documentation about `tox` in general:

<http://tox.testrun.org/>

Installation:

```
pip install -U tox
```

code hosting and issue tracking on bitbucket:

<https://bitbucket.org/hpk42/tox>



## What is tox?

tox standardizes and automates tedious test activities driven from a simple `tox.ini` file, including:

- creation and management of different virtualenv environments with different Python interpreters
- packaging and installing your package into each of them
- running your test tool of choice, be it nose, py.test or unittest2 or other tools such as “sphinx” doc checks
- testing dev packages against each other without needing to upload to PyPI

best, Holger Krekel, merlinux GmbH

## Changes 1.8 (compared to 1.7.2)

- new multi-dimensional configuration support. Many thanks to Alexander Schepanovski for the complete PR with docs. And to Mike Bayer and others for testing and feedback.
- fix issue148: remove “`__PYVENV_LAUNCHER__`” from `os.environ` when starting subprocesses. Thanks Steven Myint.
- fix issue152: set `VIRTUAL_ENV` when running test commands, thanks Florian Ludwig.
- better report if we can’t get `version_info` from an interpreter executable. Thanks Floris Bruynooghe.

## tox-1.9: refinements, fixes (+detox-0.9.4)

tox-1.9 was released to pypi, a maintenance release with mostly backward-compatible enhancements and fixes. However, tox now defaults to pip-installing only non-development releases and you have to set “`pip_pre = True`” in your `testenv` section to have it install development (“pre”) releases.

In addition, there is a new `detox-0.9.4` out which allow to run tox test environments in parallel and fixes a compat problem with `eventlet`.

Thanks to Alexander Schepanovski, Florian Schulze and others for the contributed fixes and improvements.

More documentation about tox in general:

<http://tox.testrun.org/>

Installation:

```
pip install -U tox
```

code hosting and issue tracking on bitbucket:

<https://bitbucket.org/hpk42/tox>

## What is tox?

tox standardizes and automates tedious test activities driven from a simple `tox.ini` file, including:

- creation and management of different virtualenv environments with different Python interpreters
- packaging and installing your package into each of them
- running your test tool of choice, be it nose, py.test or unittest2 or other tools such as “sphinx” doc checks
- testing dev packages against each other without needing to upload to PyPI

best, Holger Krekel, merlinux GmbH

## 1.9.0

- fix issue193: Remove `--pre` from the default `install_command`; by default tox will now only install final releases from PyPI for unpinned dependencies. Use `pip_pre = true` in a testenv or the `--pre` command-line option to restore the previous behavior.
- fix issue199: fill `resultlog` structure ahead of virtualenv creation
- refine determination if we run from Jenkins, thanks Borge Lanes.
- echo output to stdout when `--report-json` is used
- fix issue111: add a `skip_install` per-testenv setting which prevents the installation of a package. Thanks Julian Krause.
- fix issue124: ignore command exit codes; when a command has a “-” prefix, tox will ignore the exit code of that command
- fix issue198: fix broken `envlist` settings, e.g. `{py26,py27}{-lint,}`
- fix issue191: lessen factor-use checks

## tox-2.0: plugins, platform, env isolation

tox-2.0 was released to pypi, a major new release with *mostly* backward-compatible enhancements and fixes:

- experimental support for plugins, see <https://testrun.org/tox/latest/plugins.html> which includes also a refined internal registration mechanism for new testenv ini options. You can now ask tox which testenv ini parameters exist with `tox --help-ini`.
- ENV isolation: only pass through very few environment variables from the tox invocation to the test environments. This may break test runs that previously worked with tox-1.9 – you need to either use the `setenv` or `passenv` ini variables to set appropriate environment variables.
- PLATFORM support: you can set `platform=REGEX` in your testenv sections which lets tox skip the environment if the REGEX does not match `sys.platform`.
- tox now stops execution of test commands if the first of them fails unless you set `ignore_errors=True`.

Thanks to Volodymyr Vitvitski, Daniel Hahler, Marc Abramowitz, Anthon van der Neuth and others for contributions.

More documentation about tox in general:

<http://tox.testrun.org/>

Installation:

```
pip install -U tox
```

code hosting and issue tracking on bitbucket:

<https://bitbucket.org/hpk42/tox>

## What is tox?

tox standardizes and automates tedious test activities driven from a simple `tox.ini` file, including:

- creation and management of different virtualenv environments with different Python interpreters

- packaging and installing your package into each of them
- running your test tool of choice, be it nose, py.test or unittest2 or other tools such as “sphinx” doc checks
- testing dev packages against each other without needing to upload to PyPI

best, Holger Krekel, merlinux GmbH

## 2.0.0

- (new) introduce environment variable isolation: tox now only passes the PATH and PIP\_INDEX\_URL variable from the tox invocation environment to the test environment and on Windows also SYSTEMROOT, PATHEXT, TEMP and TMP whereas on unix additionally TMPDIR is passed. If you need to pass through further environment variables you can use the new `passenv` setting, a space-separated list of environment variable names. Each name can make use of fnmatch-style glob patterns. All environment variables which exist in the tox-invocation environment will be copied to the test environment.
- a new `--help-ini` option shows all possible testenv settings and their defaults.
- (new) introduce a way to specify on which platform a testenvironment is to execute: the new per-venv “platform” setting allows to specify a regular expression which is matched against `sys.platform`. If platform is set and doesn’t match the platform spec in the test environment the test environment is ignored, no setup or tests are attempted.
- **(new) add per-venv “ignore\_errors” setting, which defaults to False.** If `True`, a non-zero exit code from one command will be ignored and further commands will be executed (which was the default behavior in tox < 2.0). If `False` (the default), then a non-zero exit code from one command will abort execution of commands for that environment.
- show and store in json the version dependency information for each venv
- remove the long-deprecated “distribute” option as it has no effect these days.
- fix issue233: avoid hanging with tox-setuptools integration example. Thanks simonb.
- fix issue120: allow substitution for the commands section. Thanks Volodymyr Vitvitski.
- fix issue235: fix `AttributeError` with `-installpkg`. Thanks Volodymyr Vitvitski.
- tox has now somewhat pep8 clean code, thanks to Volodymyr Vitvitski.
- fix issue240: allow to specify empty argument list without it being rewritten to “.”. Thanks Daniel Hahler.
- introduce experimental (not much documented yet) plugin system based on pytest’s externalized “pluggy” system. See `tox/hookspeps.py` for the current hooks.
- introduce `parser.add_testenv_attribute()` to register an ini-variable for testenv sections. Can be used from plugins through the `tox_add_option` hook.
- rename internal files – tox offers no external API except for the experimental plugin hooks, use tox internals at your own risk.
- DEPRECATE `distshare` in documentation

tox-2.4.0 brings some fixes and new features, see the changelog below. Docs are now at:

<https://tox.readthedocs.org>

And thanks to Ronny Pfannschmidt the tox repository is now on github:

<https://github.com/tox-dev/tox>

Also many thanks to Oliver Bestwalter, Alex Grönholm, Stefan Obermann, Danielle Jenkins, Ted Shaw, Andrzej Ostrowski and Florian Bruhin who helped with the release particularly during the testing sprint we had in June 2016.

have testing fun, holger krekel

## 2.4.0

- remove PYTHONPATH from environment during the install phase because a tox-run should not have hidden dependencies and the test commands will also not see a PYTHONPATH. If this causes unforeseen problems it may be reverted in a bugfix release. Thanks Jason R. Coombs.
- fix issue352: prevent a configuration where envdir==toxindir and refine docs to warn people about changing “envdir”. Thanks Oliver Bestwalter and holger krekel.
- fix issue375, fix issue330: warn against tox-setup.py integration as “setup.py test” should really just test with the current interpreter. Thanks Ronny Pfannschmidt.
- fix issue302: allow cross-testenv substitution where we substitute with {x, y} generative syntax. Thanks Andrew Pashkin.
- fix issue212: allow escaping curly brace chars “{” and “}” if you need the chars “{” and “}” to appear in your commands or other ini values. Thanks John Vandenberg.
- addresses issue66: add --workdir option to override where tox stores its “.tox” directory and all of the virtualenv environment. Thanks Danring.
- introduce per-venv list\_dependencies\_command which defaults to “pip freeze” to obtain the list of installed packages. Thanks Ted Shaw, Holger Krekel.
- close issue66: add documentation to jenkins page on how to avoid “too long shebang” lines when calling pip from tox. Note that we can not use “python -m pip install X” by default because the latter adds the CWD and pip will think X is installed if it is there. “pip install X” does not do that.
- new list\_dependencies\_command to influence how tox determines which dependencies are installed in a testenv.
- (experimental) New feature: When a search for a config file fails, tox tries loading setup.cfg with a section prefix of “tox”.
- fix issue275: Introduce hooks tox\_runttest\_pre` and tox\_runttest\_post which run before and after the tests of a venv, respectively. Thanks to Matthew Schinckel and itxaka serrano.
- fix issue317: evaluate minversion before tox config is parsed completely. Thanks Sachi King for the PR.
- added the “extras” environment option to specify the extras to use when doing the sdist or develop install. Contributed by Alex Grönholm.
- use pytest-catchlog instead of pytest-capturelog (latter is not maintained, uses deprecated pytest API)

## Less announcing, more changelogging

With version 2.5.0 we dropped creating special announcement documents and rely on communicating all relevant changes through the [CHANGELOG](https://pypi.org/project/tox/). See <https://pypi.org/project/tox/> for a rendered version of the last changes containing links to the important issues and pull requests that were integrated into the release.

Happy testing, The tox maintainers

**t**

`tox.hookspecs`, 51



**A**

`add_argument()` (tox.config.Parser method), 52  
`add_testenv_attribute()` (tox.config.Parser method), 52  
`add_testenv_attribute_obj()` (tox.config.Parser method), 52  
`alwayscopy=TruelFalse`  
configuration value, 26  
`args_are_paths=BOOL`  
configuration value, 26

**B**

`basepython=NAME-OR-PATH`  
configuration value, 24

**C**

`changedir=path`  
configuration value, 25  
`commands=ARGVLIST`  
configuration value, 24  
`Config` (class in tox.config), 52  
`config` (tox.config.TestenvConfig attribute), 53  
configuration value  
`alwayscopy=TruelFalse`, 26  
`args_are_paths=BOOL`, 26  
`basepython=NAME-OR-PATH`, 24  
`changedir=path`, 25  
`commands=ARGVLIST`, 24  
`deps=MULTI-LINE-LIST`, 25  
`description=SINGLE-LINE-TEXT`, 27  
`downloadcache=path`, 26  
`envdir`, 27  
`envlist=CSV`, 24  
`envlogdir=path`, 27  
`envtmpdir=path`, 27  
`extras=MULTI-LINE-LIST`, 27  
`ignore_errors=TruelFalse`(default), 25  
`ignore_outcome=BOOL`, 27  
`indexserver`, 27  
`install_command=ARGV`, 24

`list_dependencies_command`, 25  
`passenv=SPACE-SEPARATED-GLOBNAMES`, 26  
`pip_pre=TruelFalse`(default), 25  
`platform=REGEX`, 26  
`recreate=TruelFalse`(default), 26  
`setenv=MULTI-LINE-LIST`, 26  
`sitepackages=TruelFalse`, 26  
`skip_install=BOOL`, 27  
`skip_missing_interpreters=BOOL`, 24  
`usedevelop=BOOL`, 27  
`whitelist_externals=MULTI-LINE-LIST`, 25

**D**

`deps=MULTI-LINE-LIST`  
configuration value, 25  
`description=SINGLE-LINE-TEXT`  
configuration value, 27  
`downloadcache=path`  
configuration value, 26

**E**

`envconfigs` (tox.config.Config attribute), 52  
`envdir`  
configuration value, 27  
`envlist=CSV`  
configuration value, 24  
`envlogdir=path`  
configuration value, 27  
`envname` (tox.config.TestenvConfig attribute), 53  
`envpython` (tox.config.TestenvConfig attribute), 53  
`envtmpdir=path`  
configuration value, 27  
`extras=MULTI-LINE-LIST`  
configuration value, 27

**F**

`factors` (tox.config.TestenvConfig attribute), 53

**G**

`get_envbindir()` (tox.config.TestenvConfig method), 53

get\_envpython() (tox.config.TestenvConfig method), 53  
get\_envsitepackagesdir() (tox.config.TestenvConfig method), 53  
get\_installpkg\_path() (tox.session.Session method), 53  
getcommandpath() (tox.venv.VirtualEnv method), 53  
getvenv() (tox.session.Session method), 54

## I

ignore\_errors=True|False(default)  
configuration value, 25  
ignore\_outcome=BOOL  
configuration value, 27  
indexserver  
configuration value, 27  
install\_command=ARGV  
configuration value, 24  
installpkg() (tox.session.Session method), 54

## L

list\_dependencies\_command  
configuration value, 25

## M

missing\_subs (tox.config.TestenvConfig attribute), 53

## N

name (tox.venv.VirtualEnv attribute), 53

## O

option (tox.config.Config attribute), 52

## P

Parser (class in tox.config), 52  
passenv=SPACE-SEPARATED-GLOBNAMES  
configuration value, 26  
path (tox.venv.VirtualEnv attribute), 53  
pip\_pre=True|False(default)  
configuration value, 25  
platform=REGEX  
configuration value, 26  
Python Enhancement Proposals  
PEP 386, 18  
python\_info (tox.config.TestenvConfig attribute), 53

## R

recreate=True|False(default)  
configuration value, 26

## S

Session (class in tox.session), 53  
setenv=MULTI-LINE-LIST  
configuration value, 26  
sitepackages=True|False

configuration value, 26  
skip\_install=BOOL  
configuration value, 27  
skip\_missing\_interpreters=BOOL  
configuration value, 24

## T

TestenvConfig (class in tox.config), 53  
tox.hookspeccs (module), 51  
tox\_adoption() (in module tox.hookspeccs), 51  
tox\_configure() (in module tox.hookspeccs), 51  
tox\_get\_python\_executable() (in module tox.hookspeccs), 51  
tox\_runtest() (in module tox.hookspeccs), 51  
tox\_runtest\_post() (in module tox.hookspeccs), 51  
tox\_runtest\_pre() (in module tox.hookspeccs), 51  
tox\_testenv\_create() (in module tox.hookspeccs), 51  
tox\_testenv\_install\_deps() (in module tox.hookspeccs), 52

## U

update() (tox.venv.VirtualEnv method), 53  
usedevelop=BOOL  
configuration value, 27

## V

VirtualEnv (class in tox.venv), 53

## W

whitelist\_externals=MULTI-LINE-LIST  
configuration value, 25